


# LED Tubular Lamp



## Dimmable LED T8 INSTAlite DIM Glass



- Energy saving up to 46% compare to F32T8 system
- Perfect retrofit traditional lamps for INSTANT START, RAPID START, PROGRAMMED START and 0-10V DIMMABLE PROGRAMMED START ballast circuit
- 280° beam angle allows fixture to maintain original light distribution by parabolic reflector
- Smooth operation even at low temperatures down to -20°C
- No mercury and hazardous substances
- Compatible with most common instant start electronic ballasts (Refer to the ballast compatibility list)
- No re-wiring cost
- Ra90 available on request
- Full glass body with safety approval



Model	Voltage	Wattage	Color	Color Temp	CRI (Ra)	Lumen	Beam Angle	Length MOL (in.)
LED F8T8/830/G/NA/ISD	110-277V	8W	Warm White	3000K	≥80	940 lm	280°	24
LED F8T8/835/G/NA/ISD	110-277V	8W	White	3500K	≥80	940 lm	280°	24
LED F8T8/840/G/NA/ISD	110-277V	8W	Neutral White	4000K	≥80	970 lm	280°	24
LED F8T8/850/G/NA/ISD	110-277V	8W	Cool White	5000K	≥80	990 lm	280°	24
LED F15T8/830/G/NA/ISD	110-277V	15W	Warm White	3000K	≥80	1770 lm	280°	48
LED F15T8/835/G/NA/ISD	110-277V	15W	White	3500K	≥80	1770 lm	280°	48
LED F15T8/840/G/NA/ISD	110-277V	15W	Neutral White	4000K	≥80	1820 lm	280°	48
LED F15T8/850/G/NA/ISD	110-277V	15W	Cool White	5000K	≥80	1860 lm	280°	48
LED F17T8/830/G/NA/ISD	110-277V	17W	Warm White	3000K	≥80	2000 lm	280°	48
LED F17T8/835/G/NA/ISD	110-277V	17W	White	3500K	≥80	2000 lm	280°	48
LED F17T8/840/G/NA/ISD	110-277V	17W	Neutral White	4000K	≥80	2050 lm	280°	48
LED F17T8/850/G/NA/ISD	110-277V	17W	Cool White	5000K	≥80	2100 lm	280°	48