

MORE PRODUCTION SAME EXTRAORDINARY CUT.

The Groundsmaster® 4500-D and 4700-D continue to provide the clean quality of cut of a reel mower but with the maintenance ease of a rotary. Toro's exclusive new SmartCool™ system keeps your machine on the job and moving forward. Before things get too hot, SmartCool briefly reverses the cooling fan to blast chaff and debris from the intake screens. Smart? You know it. Cool? Definitely! With a 55 hp (41 kW) turbo-diesel under the hood and the new Smart Power™ technology that maximizes power to the Contour™ Plus cutting decks, the Groundsmaster 4500-D and 4700-D are an unprecedented blend of powerful productivity and refined results.



Groundsmaster® 4500-D



Groundsmaster® 4700-D

toro.com/contour



F E A T U R E S

Groundsmaster® 4500-D/4700-D

- 55 hp (41 kW) Yanmar® engine, Tier 4 Final Compliant, turbo-diesel engine.
- Patented Contour™ Plus rotary cutting units for virtually no scalping.
- Full-length striping rear rollers.
- 9' (2.7 m) and 12.5' (3.8 m) width of cut.
- 6.5" (16.5 cm) cutting unit overlap to eliminate streaking.
- Smart Power™ – optimized mowing in all conditions.
- SmartCool™ system with auto reversing cooling fan.
- 4-way adjustable Seat and Air Ride Suspension.
- Integrated ControlHub™ with fingertip electronic controls.
- InfoCenter™ displays simple operating info while monitoring machine health.
- Full-time, bi-directional 4WD.
- 4-wheel drive traction assist (optional).
- Reliable planetary gear wheel drive system.



GROUNDMASTER 4500-D, TIER 4 DIESEL, MODEL 30881

GROUNDMASTER 4700-D, TIER 4 DIESEL, MODEL 30882

ENGINE	Yanmar® 4-cylinder liquid-cooled, turbo-charged diesel. Power: 55 hp (41.1 kW) gross power at rated speed of 2700 rpm. Torque peak: 125 ft-lbs (169 Nm) @ 2000 rpm. Displacement: 127 cu-in (2.1 liters). EPA Tier IV Final Compliant.		
AIR CLEANER	Dry, replaceable primary and safety elements.		
RADIATOR	Rear-mount, single pass, 7-row, 6.3 fins per inch, 13 quart (12.3 liters) capacity.		
FUEL CAPACITY	22 gallons (83 liters) diesel fuel. Biodiesel ready for use up to B-20 (20% biodiesel and 80% petroleum blend).		
TRACTION DRIVE	Parallel hydrostatic, closed-loop system with full-time 4WD forward/reverse in low (mow) and high (transport) range with optional full-time, automatic traction flow divider (forward only) (Model 30876). Variable displacement piston pump with electronic servo control powers dual speed piston motor drive into double reduction planetary in front, and mechanical axle in rear. Smart Power™ feature controls traction speed to maintain optimal cutting blade speed.		
HYDRAULICS/COOLING	8.25 gallon (31.3 liter) capacity with 10 micron remote spin-on filter, 9 row single pass cooler with tilt out for cleaning. Variable speed hydraulic fan drive with automatic (based on coolant and oil temps) and manual reversing capabilities.		
DIAGNOSTICS	Diagnostics pressure test ports: forward and reverse traction, deck circuit 1 & 2, reverse 4WD, lift, steering, traction charge, and counter balance.		
GROUND SPEED	Transport: 0-13 mph (0-21 km/h) forward, 0-6.2 mph (0-10 km/h) reverse. Mow: 0-7 mph (0-11.3 km/h) forward, 0-3.5 mph (0-5.6 km/h) reverse.		
TIRES	Front: 29 x 14-15, 6-ply ultra-tread. Rear: 20 x 10-10, 4-ply multi-trac tread.		
MAIN FRAME	All welded formed-steel frame with integral tie-down anchors.		
BRAKES	Mechanically actuated, internal wet disc brakes on input to each planetary drive. Individual foot-operated steering brake control of left and right wheel. Lock pedals together and latch to engage parking brake.		
SEAT	Premium seat with adjustments for operator weight via air ride suspension, seat fore/aft position, seat back angle, arm rest height and retractable seat belt.		
STEERING	Power steering with dedicated power source, tilt steering.		
INTSTRUMENTATION	InfoCenter™ System: onboard LCD display shows gauges, alerts/faults, service reminders, electrical system diagnostics. Indicates fuel level, coolant temperature, intake temperature, low oil pressure, alternator, engine hours, engine rpm, hydraulic oil temperature, and voltage.		
CONTROLS	Ignition switch, throttle switch, mow/transport range selection switch, PTO switch, light switch. Foot-operated traction pedal, individual foot-operated steering brake control of left and right wheels with parking brake lock. One 2-position switch (GM 4500-D). Three 2-position switches (GM 4700-D).		
ELECTRICAL	12 volt battery with 540 cold cranking amps, 55 amp alternator. Overload protection with automotive-type fuses.		
INTERLOCKS	Prevents engine from starting unless traction pedal is in neutral and deck is disengaged. If operator leaves seat with deck engaged, engine stops. Mowing only permitted in low range. Engine stops if parking brake engaged and traction pedal not in neutral.		
OPERATOR AREA	Beverage holder, radio holder/mobile phone holder, 12 volt power outlet, open compartment for tools, jackets, golf balls, etc. under control arm.		
WORK LIGHTS	Standard.		
ROPS	2-post standard.		
DIMENSIONS WITH CUTTING UNITS		GM 4500-D	GM 4700-D
	Overall length with decks down	145.8" (370 cm)	145.8" (370 cm)
	Overall width, lowered/raised	112.8" (286 cm)/88.3" (224 cm)	153.8" (391 cm)/88.3" (224 cm)
	Height with 2-post ROPS	85" (216 cm)	85" (216 cm)
	Wheelbase	67.5" (172 cm)	67.5" (172 cm)
	Track width, front/rear	88.3" (224 cm)/55.5" (141 cm)	88.3" (224 cm)/55.5" (141 cm)
	Ground clearance	6" (15.3 cm)	6" (15.3 cm)
WEIGHT	4400 lbs (1995 kg) - with full fluids.		4950 lbs (2245 kg) - with full fluids.
FUEL ECONOMY**	Acres per gallon - 3.4 (12.8 acres per liter) Mowing range - 13.8 hours Fuel consumption - 1.6 Gal/Hr (6.06 L/Hr)		Acres per gallon - 4.4 (16.7 acres per liter) Mowing range - 12.9 hours Fuel consumption - 1.7 Gal/Hr (6.44 L/Hr)
SAFETY	Complies with American National Standards Institute (ANSI B71.4-2004) and applicable ISO EN 5395 (CE) standards (machine directive 89/392, 91/368, 93/44, 84/538, 89/336) requirements.		
WARRANTY	Two-year limited.		
ACCESSORIES	Atomic mulching blades (107-0235-03), white sunshade (30349), red sunshade (30552), operator fan kit (110-8804), 4WD flow divider kit (30876), rear roller scraper kit, 2 post ROPS extension, windscreen, 90 amp alternator kit (115-8473), mulching kit (30836).		

GROUNDMASTER 4500-D, TIER 4 DIESEL, MODEL 30881

GROUNDMASTER 4700-D, TIER 4 DIESEL, MODEL 30882

CUTTING UNITS

TYPE	Five Contour™ Plus 22" (55.9 cm), rear-discharge rotary cutting units with rear rollers.	Seven Contour™ Plus 27" (68.6 cm), rear-discharge rotary cutting units with rear rollers.
WIDTH OF CUT	109" (277 cm), overlap 6.5" (16.5 cm), overhang 10.4" (26.4 cm).	Overall: 150" (381 cm), 109" (277 cm) with deck 6 and 7 raised. Overlap 6.5" (16.5 cm), overhang 30.9" (78.4 cm).
HEIGHT OF CUT	.75"-4" (1.9-10.2 cm) in .25" (.6 cm) increments.	
CONSTRUCTION	10-gauge steel constructed chambers with 12-gauge welded reinforcements. 1.5" (3.8 cm) square x .25" (.6 cm) wall tube with 7-gauge side supports. Spindle support 3/16" (.48 cm) high-strength steel and 10-gauge exterior channels.	
SPINDLE ASSEMBLY	Ductile cast iron spindle housing. Dual greaseable tapered roller bearings. 1.25" (3.2 cm) diameter solid cold-finished steel spindle shaft. Splined connection between spindle shaft and pulley. Welded blade retainer plus anti-scalp cups.	
GROUND FOLLOWING	6" (15.3 cm) anti-scalp cups on each blade. On each deck: two 5" (12.7 cm) diameter front rollers, one 3" (7.6 cm) diameter rear roller.	
BLADES	27" (68.6 cm) long, 2.5" (6.4 cm) wide, .25" (.64 cm) thick. Standard combo blade optional Atomic Blade for leaf mulching.	
WING PROTECTION	Groundsmaster 4700-D has an impact absorption device on wing decks 6 and 7.	

*Specifications and design subject to change without notice.

**Dependent on operator and turf conditions, assumes 85% efficiency for overlaps and turns. Certification complies with ANSI B71.4-1999 and applicable CE directives.

Warranty: Two-year limited warranty. Refer to operator's manual for further details.

The Groundsmaster 4500-D and 4700-D are manufactured in Tomah, WI ISO 9002 Certified Plant.



toro.com

Worldwide Headquarters
 The Toro Company
 8111 Lyndale Ave. So.
 Bloomington, MN 55420 U.S.A.
 Phone: (1) 952 888 8801
 Fax: (1) 952 887 8258

Printed in U.S.A.
 ©2016 The Toro Company.
 All Rights Reserved.
 200-7092 GB



facebook.com/ToroCompany
 twitter.com/TheToroCompany
 youtube.com/ToroCompanyEurope



Count on it.