

**DEVELOP**

Dynamic balance

[www.develop.eu](http://www.develop.eu)



# ineo+ 750i



- > Colour A3  
multifunctional
- > Up to 75 ppm

## Option diagram

### 1 Enhanced Features

PDF enhancements	LK-102v3
OCR text recognition	LK-105v4
Barcode fonts	LK-106
Unicode fonts	LK-107
OCR A and B fonts	LK-108
Document converter pack	LK-110v2
ThinPrint® client	LK-111
Serverless pull printing	LK-114
Trusted Platform Module	LK-115v2
Antivirus	LK-116
FOIP activation	LK-117



### 2 Connectivity

Fax board	FK-514	x2
Wireless LAN	UK-221	
USB I/F kit	EK-608	OR
USB I/F kit	EK-609	
Fiery controller	IC-420	
Interface kit for IC-420	VI-516	
Biometric authentication	AU-102	OR
ID card reader		
Mount kit	MK-735	

### 3 Others

Working table	WT-506
Upright panel	WT-519
10-Key pad	KP-102
Security kit	SC-509
Replacement SSD	EM-908
Keyboard holder	KH-102
Air cleaning unit	CU-102

### 4 Media Input

Large capacity tray	LU-303	OR
Large capacity tray	LU-205	
Banner tray	BT-C1e	

### 5 Media output

Output tray	OT-514	OR	Staple finisher	FS-539	OR	Staple finisher	FS-540
			Relay unit	RU-519	OR	Relay unit	RU-519
			Booklet finisher	FS-539SD	OR	Booklet finisher	FS-540SD
			Relay unit	RU-519		Relay unit	RU-519
			Punch kit for FS-539/SD	PK-524		Punch kit for FS-540/SD	PK-526
						Post inserter for FS-540/SD	PI-507
						Job separator for FS-540/SD	JS-602
						Z-fold unit for FS-540/SD	ZU-609

#### legend

- Mandatory option
- Option
- This option can only be installed with the respective option above it

## Finishing functionalities



- Corner stapling
- Corner stapling (offline)
- Two-point stapling
- Two-hole punching
- Four-hole punching
- Duplex
- Combined mixplex/mixmedia
- Half-fold
- Sheet insertion, report
- Letterfold
- Booklet
- Offset sorting
- Z-fold
- Banner printing 1.2m

## Description

### Enhanced Features

LK-102v3 PDF enhancements	PDF/A(1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint® client	Print data compression for reduced network impact
LK-114 Serverless pull printing	Secure and Follow Me printing solution requiring no server application
LK-115v2 Trusted Platform Module	Trusted Platform Module for protection of data encryption and decryption
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all incoming and outgoing data
LK-117 FOIP activation	Fax over IP networks (T.38), requires fax kit

### Connectivity

FK-514 Fax board	Super G3 fax, digital fax functionality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
IC-420 Fiery controller	Professional colour print controller
VI-516 Interface kit for IC-420	Fiery controller interface card
AU-102 Biometric authentication	Finger vein scanner
ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader

### Others

WT-506 Working table	Authentication device placement
WT-519 Working table	Working table for upright panel
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 Replacement SSD	1TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard
CU-102 Air cleaning unit	Improving indoor air quality by reduced emission

### Media Input

LU-303 Large capacity tray	3,000 sheets, A4, 52–256 g/m <sup>2</sup>
LU-205 Large capacity tray	2,500 sheets, A4–SRA3, 52–256 g/m <sup>2</sup>
BT-C1e Banner tray	Multipage banner feeding

### Media Output

OT-514 Output tray	Output tray used instead of finisher
FS-539 Staple finisher	50 sheets stapling; 3,200 sheets max. output
FS-539SD Booklet finisher	50 sheets stapling; 20 sheets booklet finisher; 2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/4 hole punching; autoswitching
FS-540 Staple finisher	100 sheets stapling; 3,200 sheets max. output
FS-540SD Booklet finisher	100 sheets stapling; 20 sheets booklet finisher; 2,700 sheets max. output
PK-526 Punch kit for FS-540/SD	2/4 hole punching; autoswitching
RU-519 Relay unit	For FS-539/SD or FS-540/SD installation
PI-507 Post inserter for FS-540/SD	Cover insertion; post finishing
JS-602 Job separator for FS-540/SD	Separation of fax output; etc.
ZU-609 Z-fold unit for FS-540/SD	Z-fold for A3 prints

## Technical specifications

### SYSTEM SPECIFICATIONS

System speed A4	Up to 75/70 ppm (mono/colour)
System speed A3	Up to 37/35 ppm (mono/colour)
Autoduplex speed A4	Up to 75/70 ppm (mono/colour)
1st page out time A4	2.8/3.8 sec. (mono/colour)
Warm-up time	Approx. 17/18 sec. (mono/colour) <sup>1</sup>
Imaging technology	Laser
Toner technology	HD polymerised toner
Panel size/resolution	10.1" / 1024 x 600
System memory	8,192 MB (standard/max)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP(S); Bonjour
Automatic document feeder	Up to 300 originals; A6–A3; 35–210 g/m <sup>2</sup> ; Dualscan ADF
ADF double feed detection	Standard
Printable paper size	A6–SRA3; customized paper sizes; banner paper max. 1,200 x 297 mm
Printable paper weight	52–300 g/m <sup>2</sup>
Paper input capacity	3,650 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1x 500; A6–A3; custom sizes; 52–256 g/m <sup>2</sup> 1x 500; A5–SRA3; custom sizes; 52–256 g/m <sup>2</sup> 1x 1,500; A5–A4; 52–256 g/m <sup>2</sup> 1x 1,000; A5–A4; 52–256 g/m <sup>2</sup>
Large capacity tray (optional)	1x 3,000; A4; 52–256 g/m <sup>2</sup> 1x 2,500; A4–SRA3; custom sizes; 52–256 g/m <sup>2</sup>

### SYSTEM SPECIFICATIONS

Manual bypass	150 sheets; A6–SRA3; custom sizes; banner; 60–300 g/m <sup>2</sup>
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold; Letter-fold; Booklet; Post insertion; Z-fold
Automatic duplexing	A6–SRA3; 52–256 g/m <sup>2</sup>
Output capacity	Up to 200 sheets / up to 3,300 sheets (standard/max)
Stapling	Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m <sup>2</sup> )
Stapling output capacity	Max. 200 sets
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 50 sets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m <sup>2</sup> )
Booklet output capacity	Max. 35 booklets; unlimited (without tray)
Duty cycle (monthly)	Rec. 80,000 pages; Max. <sup>2</sup> 300,000 pages
Toner lifetime	Black up to 45,000 pages CMY up to 45,000 pages
Imaging unit lifetime	Black up to 240,000/1,000,000 pages (drum/developer) CMY up to 165,000/1,000,000 pages (drum/developer)
Power consumption	220–240 V / 50/60 Hz; Less than 2.10 kW
System dimension (W x D x H)	615 x 688 x 1207 mm (without options)
System weight	Approx. 160.0 kg (without options)

**PRINTER SPECIFICATIONS**

<b>Print resolution</b>	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
<b>Page description language</b>	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
<b>Operating systems</b>	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Macintosh OS X 10.11 or later; Unix; Linux; Citrix
<b>Printer fonts</b>	80 PCL Latin; 137 PostScript 3 Emulation Latin
<b>Mobile printing</b>	AirPrint (iOS); Mopria (Android) optional: WiFi Direct

**PRINTER SPECIFICATIONS (OPTIONAL)**

<b>Print controller</b>	Embedded Fiery IC-420
<b>Controller CPU</b>	AMD GX-424CC @ 2.4 GHz
<b>Memory/HDD</b>	4,096 MB / 500 GB
<b>Page description language</b>	Adobe PostScript 3 (CPSI 3020); PCL 6; PCL 5c
<b>Operating systems</b>	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Macintosh OS X 10.11 or later; Linux

**SCANNER SPECIFICATIONS**

<b>Scan speed</b>	Up to 140/140 ipm in simplex (mono/colour) Up to 280/280 ipm in duplex (mono/colour)
<b>Scan resolution</b>	Up to 600 x 600 dpi
<b>Scan modes</b>	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-to-DPWS; Scan-to-URL; TWAIN scan
<b>File formats</b>	JPEG; TIFF; PDF, Compact PDF; Encrypted PDF; XPS; Compact XPS; PPTX optional: Searchable PDF; PDF/A 1a and 1b; Searchable DOCX/PPTX/XLSX
<b>Scan destinations</b>	2,000 destinations + 100 groups; LDAP support

**COPIER SPECIFICATIONS**

<b>Copy resolution</b>	600 x 600 dpi
<b>Gradation</b>	256 gradations
<b>Multicopy</b>	1-9,999
<b>Original format</b>	Max. A3
<b>Magnification</b>	25-400% in 0.1% steps; Auto-zooming

**FAX SPECIFICATION**

<b>Fax standard</b>	Super G3 (optional)
<b>Fax transmission</b>	Analogue; i-Fax; Colour i-Fax; IP-Fax
<b>Fax resolution</b>	Up to 600 x 600 dpi
<b>Fax compression</b>	MH; MR; MMR; JBIG
<b>Fax modem</b>	Up to 33.6 Kbps
<b>Fax destinations</b>	2,000 single + 100 groups

**USER BOX SPECIFICATIONS**

<b>Storable documents</b>	Up to 3,000 documents or 10,000 pages
<b>Type of user boxes</b>	Public; Personal (with password or authentication); Group (with authentication)
<b>Type of system boxes</b>	Secure print; Encrypted PDF print; Fax receipt; Fax polling

**SYSTEM FEATURES**

<b>Security</b>	ISO 15408 HCD-PP Common Criteria (in evaluation); IP filtering and port blocking; SSL3 and TLS1.0/1.1/1.2 network communication; IPsec support; IEEE 802.1x support; User authentication; Authentication log; Secure print; Kerberos; Hard drive overwrite; Hard drive data encryption (AES 256); Confidential fax; Print user data encryption optional: Antivirus realtime scanning (Bitdefender®); Copy protection (Copy Guard; Password Copy)
<b>Accounting</b>	Up to 1,000 user accounts; Active Directory support (user name + password + e-mail + smb folder); User function access definition; Authentication by mobile device (Android) optional: Biometric authentication (finger vein scanner); ID card authentication (ID card reader); Authentication by mobile device (iOS)
<b>Software</b>	store+find (opt.); convert+share (opt.); Device Manager; Box Operator; Data Administrator (user accounts & cost centres); Card solutions (opt.); EveryonePrint (opt.)

<sup>1</sup> Warm-up time may vary depending on the operating environment and usage

<sup>2</sup> If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed



**DEVELOP** Konica Minolta Business Solutions Europe GmbH  
Europaallee 17 30855 Langenhagen Germany Phone +49 511 7404-0 www.develop.eu



**Smythe Business Machines**

**6 Harbour Court  
Belfast, BT3 9HB  
t: 028 9020 7000  
f: 028 9020 7001  
e: info@sbmonline.co.uk**

- All specifications refer to A4-size paper of 80 g/m<sup>2</sup> quality.  
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.  
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.  
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.  
- DEVELOP and ineo are registered trademarks/product titles owned by Konica Minolta Business Solutions Europe GmbH.  
- Konica Minolta does not warrant that any specifications mentioned will be error-free.  
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.