JCW Series | Gasoline Belt Drive



Built with an all-steel frame and base plate, the JCW Series belt-driven pressure washer can handle even the toughest environments.



Pump

- Belt drive triplex piston AR pump with ceramic plungers
- Forged brass manifold
- Thermal relief valve
- Water filter with clear sleeve for screen inspection
- Stainless-steel and brass unloader with adjustable pressure (3000, 3500 & 4000-PSI models feature Mi-T-M unloader)

Frame

- Powder coated steel frame and base plate with 11/4-inch tube handles
- Two-piece belt guard for quick access to belts
- Flat-free tires

Engine

- Performance-proven engine with low-oil protection

Unit Includes:

- Quick connect nozzles 0°, 15°, 25° & 40°
- 50-foot x ³/₂-inch non-marking hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip (48-inch on 3500 & 4000-PSI models)

JCW Series | Gasoline Belt Drive



| Model Number | PSI | GPM | Displacement/Engine | Dumn | Unloader | Lance | Dimensions (LxWxH) | Ship Wt. | Net Wt. |
|----------------|------|-------|---------------------|------|-----------------------------|-------|-----------------------|-----------|-----------|
| Wouel Wallibel | rəi | urivi | Displacement/Engine | Pump | Ullivauei | Lance | DITTETISIONS (LXVXII) | Silip Wt. | IVEL VVI. |
| JCW-2403-0MHB | 2400 | 2.8 | 196cc Honda OHV | AR | Adjustable pressure | 36in. | 37.5x22x25in. | 171 lb. | 121 lb. |
| JCW-2403-0MRB | 2400 | 2.8 | 211cc Subaru OHC | AR | Adjustable pressure | 36in. | 37.5x22x25in. | 171 lb. | 121 lb. |
| JCW-2703-0MHB | 2700 | 2.4 | 196cc Honda OHV | AR | Adjustable pressure | 36in. | 37.5x22x25in. | 171 lb. | 121 lb. |
| JCW-2703-0MRB | 2700 | 2.4 | 211cc Subaru OHC | AR | Adjustable pressure | 36in. | 37.5x22x25in. | 171 lb. | 121 lb. |
| JCW-3003-2MHB | 3000 | 3.0 | 270cc Honda OHV | AR | Mi-T-M, adjustable pressure | 36in. | 39.5x28.5x26in. | 232 lb. | 178 lb. |
| JCW-3003-2MSB | 3000 | 3.0 | 265cc Subaru OHC | AR | Mi-T-M, adjustable pressure | 36in. | 39.5x28.5x26in. | 232 lb. | 178 lb. |
| JCW-3504-2MHB | 3500 | 3.7 | 389cc Honda OHV | AR | Mi-T-M, adjustable pressure | 48in. | 39.5x28.5x26in. | 245 lb. | 191 lb. |
| JCW-3504-2MSB | 3500 | 3.7 | 404cc Subaru OHC | AR | Mi-T-M, adjustable pressure | 48in. | 39.5x28.5x26in. | 245 lb. | 191 lb. |
| JCW-4004-2MHB | 4000 | 3.5 | 389cc Honda OHV | AR | Mi-T-M, adjustable pressure | 48in. | 39.5x28.5x26in. | 249 lb. | 195 lb. |
| JCW-4004-2MSB | 4000 | 3.5 | 404cc Subaru OHC | AR | Mi-T-M, adjustable pressure | 48in. | 39.5x28.5x26in. | 249 lb. | 195 lb. |

| Options: | | | | | | |
|-------------|--|-------------------------|--|--|--|--|
| Part Number | Description | Fits Models | | | | |
| CX-0005 | 48-in. insulated dual lance - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to | All models | | | | |
| | change tips | | | | | |
| CX-0082 | External bypass system - Allows more water into the system to protect from heat build-up; attaches to pump | 3000 to 4000-PSI models | | | | |
| CX-0085 | External bypass system - Allows more water into the system to protect from heat build-up; attaches to base plate | 3000 to 4000-PSI models | | | | |

| Accessories: | | | | | | |
|--------------|---|-------------|--|--|--|--|
| Part Number | Description | Fits Models | | | | |
| 50-0161 | High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up | All models | | | | |
| 851-0338 | 50-ft. x %-in. non-marking hose - For when you need extra hose for added mobility | All models | | | | |
| AW-8400-0021 | Low pressure detergent injector - Allows the user to apply the recommended detergents | All models | | | | |

