

JP Series | Gasoline Direct Drive



The powerful gasoline direct drive JP Series is designed for excellent balance and mobility, and is highly recommended for contractor jobs.



JP-3003-3MSB

Pump

- Direct drive triplex piston AR or Mi-T-M pump with ceramic plungers
- Forged brass manifold
- Thermal relief valve
- In-line water strainer
- Stainless-steel and brass Mi-T-M unloader with adjustable pressure

Frame

- Powder coated steel frame and base plate with 1 1/4-inch tube handles
- Flat-free tires

Engine

- Performance-proven engine with low-oil protection

Unit Includes:

- Quick connect nozzles – 0°, 15° & 25°
- 50-foot x 3/4-inch non-marking hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip (48-inch on 3500 & 4000-PSI models)

JP Series | Gasoline Direct Drive



Model Number	PSI	GPM	Displacement/Engine	Pump	Unloader	Lance	Dimensions (LxWxH)	Ship Wt.	Net Wt.
JP-2403-3MHB	2400	2.4	196cc Honda OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	100 lb.	75 lb.
JP-2403-3MSB	2400	2.4	211cc Subaru OHC	Mi-T-M	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	100 lb.	75 lb.
JP-2703-3MHB	2700	2.4	196cc Honda OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-2703-3MSB	2700	2.4	211cc Subaru OHC	Mi-T-M	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-3003-3MHB	3000	3.0	270cc Honda OHV	AR	Mi-T-M, adjustable pressure	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3003-3MSB	3000	3.0	265cc Subaru OHC	AR	Mi-T-M, adjustable pressure	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3504-3MHB	3500	3.5	389cc Honda OHV	AR	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-3504-3MSB	3500	3.5	404cc Subaru OHC	AR	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-4004-3MHB	4000	3.5	389cc Honda OHV	AR	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-4004-3MSB	4000	3.5	404cc Subaru OHC	AR	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.

Options:

Part Number	Description	Fits Models
CX-0005	48-in. insulated dual lance - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	All models
CX-0083	External bypass system - Allows more water into the system to protect from heat build-up	2400 to 2700-PSI models
CX-0084	External bypass system - Allows more water into the system to protect from heat build-up	3500 to 4000-PSI models

Accessories:

Part Number	Description	Fits Models
50-0161	High pressure detergent injector - High pressure washer mixes with detergent to clean even the heaviest build-up	All models
851-0338	50-ft. x 3/8-in. non-marking hose - For when you need extra hose for added mobility	All models
AW-8400-0021	Low pressure detergent injector - Allows the user to apply the recommended detergents	All models

