




Reflector Options






45° : Ø15.12"x5.71" 60° : Ø14.65"x5.87" 90° : Ø17.91"x5.12"



120° : Ø19.88"x4.92" 60° : Ø16.34"x10.63"



Lamp: 200W LED, 4000K, 125°



(Unit : inch)	(D)	(H)
60W	: Ø7.09" x 6.18"	
80W	: Ø9.06" x 7.52"	
100W	: Ø9.06" x 7.52"	
150W	: Ø10.24" x 7.91"	
200W	: Ø11.81" x 8.15"	

Features

- 60W / 80W / 100W / 150W / 200W LED Highbay
- 125° beam angle for large open area coverage
- Uniformity distribution in high ceiling application
- Separately packed reflectors for cost saving logistics
- Color Rendering Index : ≥70

Materials / Finish

- Body : Die-cast aluminium
- Lens : PC
- Reflector (optional) : Anodised aluminium
- Chips: Philips Lumileds 3030
- Driver: Meanwell

Installation / Mounting

- Pendant mount by chain
- Easy Assembly by screw fixation

Standards

- Designed and manufactured to comply international standard EN60598
- Class I Electrical
- IP65
- UL, FCC, DLC
- SAA
- PSE



Model	Voltage	Wattage	Color Temp	Beam Angle	Lumen
NH1020-3-ALB060-02	90-305V	60W	3000K	125°	6800 lm
NH1020-3-ALD060-02	90-305V	60W	4000K	125°	7200 lm
NH1020-3-ALG060-02	90-305V	60W	6500K	125°	7500 lm
NH1021-3-ALB080-02	90-305V	80W	3000K	125°	9000 lm
NH1021-3-ALD080-02	90-305V	80W	4000K	125°	9800 lm
NH1021-3-ALG080-02	90-305V	80W	6500K	125°	10400 lm
NH1022-3-ALB100-02	90-305V	100W	3000K	125°	11400 lm
NH1022-3-ALD100-02	90-305V	100W	4000K	125°	12200 lm
NH1022-3-ALG100-02	90-305V	100W	6500K	125°	13000 lm
NH1023-3-ALB150-02	90-305V	150W	3000K	125°	17500 lm
NH1023-3-ALD150-02	90-305V	150W	4000K	125°	18500 lm
NH1023-3-ALG150-02	90-305V	150W	6500K	125°	19500 lm
NH1024-3-ALB200-02	90-305V	200W	3000K	125°	24000 lm
NH1024-3-ALD200-02	90-305V	200W	4000K	125°	25000 lm
NH1024-3-ALG200-02	90-305V	200W	6500K	125°	26000 lm