



TYM T1004 WITH AGRICULTURAL TYRES

Product image shown for illustration only

# T1004

## SUPERB RANGE, UNBEATABLE VALUE

The TYM compact tractor range. Powerful, reliable, diesel engines available from 25 to 105hp mean these superb workhorses can cover a wide variety of grounds care tasks while offering unbeatable value for money.

Packed full of innovative features such as easy-to-read LED display, hydrostatic power-steering, optional weather cab, and much more, TYM tractors make the ideal choice for any discerning greenkeeper, groundsman, contractor or landscaper. Some models available with heated and air conditioned cabs, power shuttle and hydrostatic transmissions. While most models can be fitted with optional loaders and backhoes.



**Put us to the test. For a free onsite demonstration, call Reesink Turfcare on 01480 226800.**



## MODEL

### ENGINE

Manufacturer	DOOSAN INFRACORE
Model	DL03-MEA08
Engine HP (kw)-gross	100 (74.6)
PTO HP (kw)	85.8 (64.0)
Rated engine speed	2300
Number of cylinders	4
Displacement-cu.in. (cc)	208 (3409)
Air cleaner	Dual Dry

### ELECTRICAL SYSTEM

Alternator	12V, 110A
------------	-----------

### FUEL SYSTEM

Type	CRDI
------	------

### DRIVETRAIN

Transmission type	Power Shuttle & Hi/Lo shift
Number of speeds	32F / 32R
Max travelling speed, mph (km/h)	24.9 (40)
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	Wet Multi plate

### HYDRAULIC SYSTEM

Pump (type)	Dual Gear pump
Implement pump cap. gpm (L/min)	15.6 (59)
Steering pump cap. gpm (L/min)	7.1 (26.7)
Maximum total flow gpm (L/min)	22.7 (85.7)
Category, 3-point hitch	II
Hitch lift capacity, lb. (kg)	6860 (3110), 9570 (4340) Opt
at 24 inches behind link ends, lb. (kg)	5490 (2490), 6490 (2944) Opt
Lift control type	Pos/Draft/Elec
Joystick valve	Standard
No. of standard remote valves-option	3

### PTO

Type	Independent
Control	Electric/Hydro
Mid (rpm) option	N/A
Rear (rpm)	540/750/1000
Shaft diameter in. (mm)	1 3/8 (35)

### CAPACITIES

Fuel tank, U.S. gal. (L)	29.1 (110)+DEF 5.3 (20)
Cooling system U.S. qt. (L)	4.35 (16.5)
Crankcase (with filter) U.S. qt. (L)	4.22 (16)
Trans. & hydr. system, U.S. gal. (L)	19.8 (75)
Front axle qt. (L)	18.5 (17.5)

### DIMENSIONS (with standard tyres)

Overall length, in. (mm) with 3P	165.4 (4200)
Overall width, in. (mm)	86 (2185)
Wheelbase, in. (mm)	90.55 (2300)
Height to top of ROPS, in. (mm)	107 (2718)
Min. ground clearance, in. (mm)	18.3 (465)
Min. turning radius, in. (mm) with brakes	143.7 (3650)
Min. turning radius, in. (mm) w/o brakes	162 (4120)

### STANDARD TYRES

Agricultural front	13.6-24
Agricultural rear	16.9-34
Industrial front	-
Industrial rear	-

### ROLL-OVER PROTECTIVE STRUCTURES

Standard	CAB with Air conditioner
----------	--------------------------

### WEIGHT

Total weight, lb. (kg)	8410 (3815)
------------------------	-------------

