

LED Downlight



Dimmable LED Downlight ND5222-23



Features

- 10W / 12W LED Dimmable Downlight
- Recessed round, uniform distribution
- Comfort glare-free diffuser
- Color Rendering Index: ≥ 90
- TRIAC dimmable

Materials / Finish




- Body: Sheet steel with white finish
- Trim: Sheet steel with white finish
- Diffuser: Opal PC, UV protected

Installation / Mounting

- Quick installation with mounting bracket and E26 base
- Suitable for 4in / 5in / 6in recessed can
- Integral gear unit allows quick and easy installation

Standards

- Designed and manufactured to comply with international standard EN60598
- Class II Electrical
- ETL



(D) (H)
 10W : Ø4" / 5" / 6" x 3.35"
 12W : Ø5" / 6" x 3.46"



Model	Voltage	Wattage	Color Temp	Beam Angle	CRI (Ra)	Lumen	Recessed Can
ND5222-10W/927	120V	10W	2700K	90°	≥ 90	650 lm	4 in / 5 in / 6 in
ND5222-10W/930	120V	10W	3000K	90°	≥ 90	650 lm	4 in / 5 in / 6 in
ND5222-10W/940	120V	10W	4000K	90°	≥ 90	650 lm	4 in / 5 in / 6 in
ND5222-10W/950	120V	10W	5000K	90°	≥ 90	650 lm	4 in / 5 in / 6 in
ND5223-12W/927	120V	12W	2700K	90°	≥ 90	800 lm	5 in / 6 in
ND5223-12W/930	120V	12W	3000K	90°	≥ 90	800 lm	5 in / 6 in
ND5223-12W/940	120V	12W	4000K	90°	≥ 90	800 lm	5 in / 6 in
ND5223-12W/950	120V	12W	5000K	90°	≥ 90	800 lm	5 in / 6 in