



TYM T754 WITH
AGRICULTURAL TYRES

Product image shown for illustration only

T754

SUPERB RANGE, UNBEATABLE VALUE

The TYM compact tractor range. Powerful, reliable, four-cylinder diesel engines available from 25 to 105hp mean these superb workhorses can cover a wide variety of grounds care tasks while offering unbeatable value for money.

Packed full of innovative features such as easy-to-read LED display, hydrostatic power-steering, optional weather cab, and much more, TYM tractors make the ideal choice for any discerning greenkeeper, groundsman, contractor or landscaper. Some models available with heated and air conditioned cabs, power shuttle and hydrostatic transmissions. While all models can be fitted with optional loaders and backhoes.

**FREE ONSITE
DEMONSTRATION**
CALL TODAY

Put us to the test. For a free onsite demonstration, call Reesink Turfcare on 01480 226800.



T525

T293

T353

TE40

T393

T433

T503

T654

T754

T1004

MODEL

ENGINE

Manufacturer	Deutz
Model	TCD2.9
Engine HP (kw)-gross	Turbo
PTO HP (kw)	74 (55)
Rated engine speed	2200
Number of cylinders	4
Displacement-cu.in. (cc)	177.0 (2900)
Air cleaner	Dual dry

ELECTRICAL SYSTEM

Alternator	14V,95A
------------	---------

FUEL SYSTEM

Type	CRDI
------	------

DRIVETRAIN

Transmission type	Power Shuttle
Number of speeds	16F /16R
Max travelling speed, mph (km/h)	24 (39)
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	Dry single plate

HYDRAULIC SYSTEM

Pump (type)	Dual gear pump
Implement pump cap. gpm (L/min)	11.1 (42)
Steering pump cap. gpm (L/min)	4.8 (18)
Maximum total flow gpm (L/min)	15.9 (60)
Category, 3-point hitch	2
Hitch lift capacity, lb. (kg)	5130 (2327)
at 24 inches behind link ends, lb. (kg)	3426 (1554)
Lift control type	Position / Draft
Joystick valve	Standard
No. of standard remote valves-option	2

PTO

Type	Independent
Control	Electric/Hydro
Mid (rpm) option	N/A
Rear (rpm)	540/1000
Shaft diameter in. (mm)	1 3/8 (35)

CAPACITIES

Fuel tank, U.S. gal. (L)	23.8 (90)
Cooling system U.S. qt. (L)	10 (9.5)
Crankcase (with filter) U.S. qt. (L)	7.4 (7)
Trans. & hydr. system, U.S. gal. (L)	12.4 (47)
Front axle qt. (L)	17.2 (16.3)

DIMENSIONS (with standard tyres)

Overall length, in. (mm) with 3P	157.5 (4002)
Overall width, in. (mm)	73.5 (1868)
Wheelbase, in. (mm)	86.1 (2188)
Height to top of ROPS, in. (mm)	104.3 (2650)
Min. ground clearance, in. (mm)	16.8 (426)
Min. turning radius, in. (mm) with brakes	141.7 (3600)
Min. turning radius, in. (mm) w/o brakes	167 (4240)

STANDARD TYRES

Agricultural front	11.2-24
Agricultural rear	16.9-30
Industrial front	~
Industrial rear	~

ROLL-OVER PROTECTIVE STRUCTURES

Standard	CAB with AC
----------	-------------

WEIGHT

Total weight, lb. (kg)	5771 (2618)
------------------------	-------------

