



TYM T393 WITH AGRICULTURAL TYRES

Product image shown for illustration only

# T393

## SUPERB RANGE, UNBEATABLE VALUE

The TYM compact tractor range. Powerful, reliable, diesel engines available from 25 to 105hp mean these superb workhorses can cover a wide variety of grounds care tasks while offering unbeatable value for money.

Packed full of innovative features such as easy-to-read LED display, hydrostatic power-steering, optional weather cab, and much more, TYM tractors make the ideal choice for any discerning greenkeeper, groundsman, contractor or landscaper. Some models available with heated and air conditioned cabs, power shuttle and hydrostatic transmissions. While most models can be fitted with optional loaders and backhoes.



**Put us to the test. For a free onsite demonstration, call Reesink Turfcare on 01480 226800.**



## MODEL

### ENGINE

Manufacturer	YANMAR
Model	3TNV88-BDSA
Engine HP (kw)-gross	38.3 (28.2)
PTO HP (kw)	30.1 (22.1)
Rated engine speed	3000
Number of cylinders	3
Displacement-cu.in. (cc)	100.2 (1642)
Air cleaner	Dual Dry

### ELECTRICAL SYSTEM

Alternator	12V70A
------------	--------

### FUEL SYSTEM

Type	Direct Fuel Injection
------	-----------------------

### DRIVETRAIN

Transmission type	Sync/Shuttle
Number of speeds	12/F 12/R
Max travelling speed, mph (km/h)	15.0 (24.2)
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	Dry Single Plate

### HYDRAULIC SYSTEM

Pump (type)	Dual Gear pump
Implement pump cap. gpm (L/min)	6.4 (24.4)
Steering pump cap. gpm (L/min)	4.6 (17.6)
Maximum total flow gpm (L/min)	11.0 (42.0)
Category, 3-point hitch	1
Hitch lift capacity, lb. (kg)	2646 (1200)
at 24 inches behind link ends, lb. (kg)	1764 (800)
Lift control type	Position/Draft
Joystick valve	Standard
No. of standard remote valves-option	2

### PTO

Type	Independent
Control	Electric/Hydro
Mid (rpm) option	N/A
Rear (rpm)	540
Shaft diameter in. (mm)	1 3/8 (35)

### CAPACITIES

Fuel tank, U.S. gal. (L)	9.0 (34)
Cooling system U.S. qt. (L)	7.4 (7)
Crankcase (with filter) U.S. qt. (L)	6.0 (5.7)
Trans. & hydr. system, U.S. gal. (L)	8.5 (32)
Front axle qt. (L)	8.7 (8.2)

### DIMENSIONS (with standard tyres)

Overall length, in. (mm) with 3P	126 (3200)
Overall width, in. (mm)	53.5 (1360)
Wheelbase, in. (mm)	64.5 (1640)
Height to top of ROPS, in. (mm)	94.5 (2400)
Min. ground clearance, in. (mm)	12.8 (325)
Min. turning radius, in. (mm) with brakes	94.4 (2400)
Min. turning radius, in. (mm) w/o brakes	116 (2950)

### STANDARD TYRES

Agricultural front	8.0-16
Agricultural rear	12.4-24
Industrial front	27x10.5-15
Industrial rear	12.5x20

### ROLL-OVER PROTECTIVE STRUCTURES

Standard	ROPS
----------	------

### WEIGHT

Total weight, lb. (kg)	3065 (1390)
------------------------	-------------

## T393 MANUAL ROPS

Manufacturer	YANMAR
Model	3TNV88-BDSA
Engine HP (kw)-gross	38.3 (28.2)
PTO HP (kw)	30.1 (22.1)
Rated engine speed	3000
Number of cylinders	3
Displacement-cu.in. (cc)	100.2 (1642)
Air cleaner	Dual Dry

Alternator	12V70A
------------	--------

Type	Direct Fuel Injection
------	-----------------------

Transmission type	Sync/Shuttle
Number of speeds	12/F 12/R
Max travelling speed, mph (km/h)	15.0 (24.2)
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	Dry Single Plate

Pump (type)	Dual Gear pump
Implement pump cap. gpm (L/min)	6.4 (24.4)
Steering pump cap. gpm (L/min)	4.6 (17.6)
Maximum total flow gpm (L/min)	11.0 (42.0)
Category, 3-point hitch	1
Hitch lift capacity, lb. (kg)	2646 (1200)
at 24 inches behind link ends, lb. (kg)	1764 (800)
Lift control type	Position/Draft
Joystick valve	Standard
No. of standard remote valves-option	2

Type	Independent
Control	Electric/Hydro
Mid (rpm) option	N/A
Rear (rpm)	540
Shaft diameter in. (mm)	1 3/8 (35)

Fuel tank, U.S. gal. (L)	9.0 (34)
Cooling system U.S. qt. (L)	7.4 (7)
Crankcase (with filter) U.S. qt. (L)	6.0 (5.7)
Trans. & hydr. system, U.S. gal. (L)	8.5 (32)
Front axle qt. (L)	8.7 (8.2)

Overall length, in. (mm) with 3P	128 (3250)
Overall width, in. (mm)	58.0 (1475)
Wheelbase, in. (mm)	66.9 (1700)
Height to top of ROPS, in. (mm)	92.5 (2350)
Min. ground clearance, in. (mm)	12.8 (325)
Min. turning radius, in. (mm) with brakes	94.4 (2400)
Min. turning radius, in. (mm) w/o brakes	116 (2950)

Agricultural front	8.0-16
Agricultural rear	12.4-24
Industrial front	27x10.5-15
Industrial rear	12.5x20

Standard	CAB
----------	-----

Total weight, lb. (kg)	3450 (1565)
------------------------	-------------

## T393 MANUAL CAB

Manufacturer	YANMAR
Model	3TNV88-BDSA
Engine HP (kw)-gross	38.3 (28.2)
PTO HP (kw)	30.1 (22.1)
Rated engine speed	3000
Number of cylinders	3
Displacement-cu.in. (cc)	100.2 (1642)
Air cleaner	Dual Dry

Alternator	12V70A
------------	--------

Type	Direct Fuel Injection
------	-----------------------

Transmission type	Sync/Shuttle
Number of speeds	12/F 12/R
Max travelling speed, mph (km/h)	15.0 (24.2)
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	Dry Single Plate

Pump (type)	Dual Gear pump
Implement pump cap. gpm (L/min)	6.4 (24.4)
Steering pump cap. gpm (L/min)	4.6 (17.6)
Maximum total flow gpm (L/min)	11.0 (42.0)
Category, 3-point hitch	1
Hitch lift capacity, lb. (kg)	2646 (1200)
at 24 inches behind link ends, lb. (kg)	1764 (800)
Lift control type	Position
Joystick valve	Standard
No. of standard remote valves-option	2

Type	Independent
Control	Electric/Hydro
Mid (rpm) option	N/A
Rear (rpm)	540
Shaft diameter in. (mm)	1 3/8 (35)

Fuel tank, U.S. gal. (L)	9.0 (34)
Cooling system U.S. qt. (L)	7.4 (7)
Crankcase (with filter) U.S. qt. (L)	6.0 (5.7)
Trans. & hydr. system, U.S. gal. (L)	8.5 (32)
Front axle qt. (L)	8.7 (8.2)

Overall length, in. (mm) with 3P	126 (3200)
Overall width, in. (mm)	53.5 (1360)
Wheelbase, in. (mm)	66.1 (1680)
Height to top of ROPS, in. (mm)	94.5 (2400)
Min. ground clearance, in. (mm)	12.8 (325)
Min. turning radius, in. (mm) with brakes	94.4 (2400)
Min. turning radius, in. (mm) w/o brakes	116 (2950)

Agricultural front	8.0-16
Agricultural rear	12.4-24
Industrial front	27x10.5-15
Industrial rear	12.5x20

Standard	ROPS
----------	------

Total weight, lb. (kg)	3065 (1390)
------------------------	-------------

## T393 HST ROPS

Manufacturer	YANMAR
Model	3TNV88-BDSA
Engine HP (kw)-gross	38.3 (28.2)
PTO HP (kw)	28.6 (21)
Rated engine speed	3000
Number of cylinders	3
Displacement-cu.in. (cc)	100.2 (1642)
Air cleaner	Dual Dry

Alternator	12V70A
------------	--------

Type	Direct Fuel Injection
------	-----------------------

Transmission type	HST
Number of speeds	Infinite/3 Range
Max travelling speed, mph (km/h)	16.8 (27)
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	N/A

Pump (type)	Dual Gear pump
Implement pump cap. gpm (L/min)	6.4 (24.4)
Steering pump cap. gpm (L/min)	4.6 (17.6)
Maximum total flow gpm (L/min)	11.0 (42.0)
Category, 3-point hitch	1
Hitch lift capacity, lb. (kg)	2646 (1200)
at 24 inches behind link ends, lb. (kg)	1764 (800)
Lift control type	Position
Joystick valve	Standard
No. of standard remote valves-option	1

Type	Independent
Control	Electric/Hydro
Mid (rpm) option	2000
Rear (rpm)	540
Shaft diameter in. (mm)	1 3/8 (35)

Fuel tank, U.S. gal. (L)	9.0 (34)
Cooling system U.S. qt. (L)	7.4 (7)
Crankcase (with filter) U.S. qt. (L)	6.0 (5.7)
Trans. & hydr. system, U.S. gal. (L)	9.25 (35)
Front axle qt. (L)	8.7 (8.2)

Overall length, in. (mm) with 3P	126 (3200)
Overall width, in. (mm)	53.5 (1360)
Wheelbase, in. (mm)	66.1 (1680)
Height to top of ROPS, in. (mm)	94.5 (2400)
Min. ground clearance, in. (mm)	12.8 (325)
Min. turning radius, in. (mm) with brakes	94.4 (2400)
Min. turning radius, in. (mm) w/o brakes	116 (2950)

Agricultural front	8.0-16
Agricultural rear	12.4-24
Industrial front	27x10.5-15
Industrial rear	12.5x20

Standard	ROPS
----------	------

Total weight, lb. (kg)	3065 (1390)
------------------------	-------------

## T393 CAB HST

Manufacturer	YANMAR
Model	3TNV88-BDSA
Engine HP (kw)-gross	38.3 (28.2)
PTO HP (kw)	28.6 (21)
Rated engine speed	3000
Number of cylinders	3
Displacement-cu.in. (cc)	100.2 (1642)
Air cleaner	Dual Dry

Alternator	12V70A
------------	--------

Type	Direct Fuel Injection
------	-----------------------

Transmission type	HST
Number of speeds	Infinite/3 Range
Max travelling speed, mph (km/h)	16.8 (27)
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	N/A

Pump (type)	Dual Gear pump
Implement pump cap. gpm (L/min)	6.4 (24.4)
Steering pump cap. gpm (L/min)	4.6 (17.6)
Maximum total flow gpm (L/min)	11.0 (42.0)
Category, 3-point hitch	1
Hitch lift capacity, lb. (kg)	2646 (1200)
at 24 inches behind link ends, lb. (kg)	1764 (800)
Lift control type	Position
Joystick valve	Standard
No. of standard remote valves-option	1

Type	Independent
Control	Electric/Hydro
Mid (rpm) option	2000
Rear (rpm)	540
Shaft diameter in. (mm)	1 3/8 (35)

Fuel tank, U.S. gal. (L)	9.0 (34)
Cooling system U.S. qt. (L)	7.4 (7)
Crankcase (with filter) U.S. qt. (L)	6.0 (5.7)
Trans. & hydr. system, U.S. gal. (L)	9.25 (35)
Front axle qt. (L)	8.7 (8.2)

Overall length, in. (mm) with 3P	128 (3250)
Overall width, in. (mm)	58.0 (1475)
Wheelbase, in. (mm)	66.1 (1680)
Height to top of ROPS, in. (mm)	92.5 (2350)
Min. ground clearance, in. (mm)	12.8 (325)
Min. turning radius, in. (mm) with brakes	94.4 (2400)
Min. turning radius, in. (mm) w/o brakes	116 (2950)

Agricultural front	8.0-16
Agricultural rear	12.4-24
Industrial front	27x10.5-15
Industrial rear	12.5x20

Standard	CAB
----------	-----

Total weight, lb. (kg)	3450 (1565)
------------------------	-------------



Reesink Turfcare UK Limited, 1-3 Station Road, St. Neots, Cambridgeshire PE19 1QH

**T 01480 226800 E info@reesinkturfcare.co.uk W reesinkturfcare.co.uk**

Reesink Turfcare IRE Limited, Kilboggin, Nurney, Co. Kildare R51 NY22

**T 045 241963 E info@reesinkturfcare.ie**

Reesink Turfcare UK Limited is authorised and regulated by the Financial Conduct Authority. We are a credit broker, not a lender, and offer credit facilities from a panel of lenders. Product specifications and design are subject to change without prior notice.

Member of Royal Reesink