



## HD USB Headsets with Noise Canceling Mic GUV3000 & GUV3005

The GUV3000 and GUV3005 are HD USB Headsets that pair with laptops, computers, IP phones and other devices to offer high-quality sound. Ideal for remote workers and busy environments, these USB headsets feature a noise cancellation microphone that minimizes background noise to provide crisp HD audio. The GUV3000 and GUV3005 provide all day comfort thanks to adjustable headbands and soft ear cushions while audio is easily adjusted using the in-line controls. GUV series headsets are compatible with any device that offers a USB connection, including laptops and Grandstream IP phones. They support all major third-party communication platforms, apps and softphones as well as Grandstream's IPVideoTalk Meetings and Wave app. By offering crystal-clear HD audio, comfortable use and wide compatibility, the GUV series is ideal for remote workers, call centers, receptionists, sales teams and more.



HD Audio for crystal clear and easy communication



USB connection provides flexibility on any device with USB compatibility



Noise canceling technology to minimize background noise



The GUV3005 includes a busy light to indicate a call in progress



Offers an adjustable headband, in-line controls and left or right wearing style



Compatible with any USB device, supports third-party and Grandstream platforms, apps and softphone

**GUV3000****GUV3005**

	<b>GUV3000</b>	<b>GUV3005</b>
<b>Connection Type</b>	USB 2.0	USB2.0, USB-A
<b>Wearing Style</b>	Adjustable headband	
<b>Speaker</b>		
<b>Speaker Diameter</b>	27mm	27mm
<b>Impedance</b>	150(±15%)Ω	32(±15%)Ω
<b>Sensitivity</b>	95±3dB (at 1kHz 1mW)	94dB (at 1kHz 1mW)
<b>Frequency Response</b>	100Hz~7kHz	20Hz~20kHz
<b>Distortion</b>	Max: 3% & 1kHz	
<b>Default Input Power</b>	10mW	
<b>Maximum Input Power</b>	20mW	
<b>L/R Volume Level Difference Average</b>	≤3dB (at 1kHz 1mW)	
<b>Microphone</b>		
<b>Dimension</b>	Φ4.0*2.2 mm	
<b>Output Impedance</b>	<2.2 kΩ	
<b>Sensitivity</b>	-47±3dB f=1kHz,Pin=1 Pa	-44±3dB f=1kHz,Pin=1 Pa
<b>SNR</b>	≥55db f=1kHz,Pin=1Pa A-Weighted Curve	
<b>Frequency Response</b>	150Hz~6.8kHz	100kHz~10kHz
<b>Directivity</b>	Cardioid	
<b>Microphone Boom Arm Rotation</b>	310°	235°
<b>Additional Features</b>		
<b>Busy-Light</b>	No	Integrated
<b>Application Compatibility</b>	Support popular communication applications (such as Zoom, Teams, WebEx, IPVideoTalk, Grandstream Wave, Counterpath, 3CX soft phones) and IP phone devices	
<b>Temperature</b>	Storage: -40° C ~ 70° C Operating: -10° C ~ 50° C	
<b>Weight</b>	125g	192g
<b>Cable Length</b>	2 meters	
<b>Packaging</b>	Headset, Quick Start Guide	
<b>Certifications</b>	CE, FCC	