



TYM T654 WITH AGRICULTURAL TYRES

Product image shown for illustration only

T654

SUPERB RANGE, UNBEATABLE VALUE

The TYM compact tractor range. Powerful, reliable, four-cylinder diesel engines available from 25 to 105hp mean these superb workhorses can cover a wide variety of grounds care tasks while offering unbeatable value for money.

Packed full of innovative features such as easy-to-read LED display, hydrostatic power-steering, optional weather cab, and much more, TYM tractors make the ideal choice for any discerning greenkeeper, groundsman, contractor or landscaper. Some models available with heated and air conditioned cabs, power shuttle and hydrostatic transmissions. While all models can be fitted with optional loaders and backhoes.



Put us to the test. For a free onsite demonstration, call Reesink Turfcare on 01480 226800.



MODEL

ENGINE

Manufacturer	Deutz
Model	TCD2.9 L4
Engine Type	Turbo
Engine HP (kw)-gross	67 (50.0)
PTO HP (kw)	61.9 (46.1)
Rated engine speed	2200
Number of cylinders	4
Displacement-cu.in. (cc)	177.0 (2900)
Air cleaner	Dual Dry

ELECTRICAL SYSTEM

Alternator	12V, 95A
------------	----------

FUEL SYSTEM

Type	CRDI
------	------

DRIVETRAIN

Transmission type	Synchro-Shuttle
Number of speeds	F24/R24
Max travelling speed, mph (km/h)	24.3 (39.1)
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	Dry Single

HYDRAULIC SYSTEM

Pump (type)	Dual Gear Pump
Implement pump cap. gpm (L/min)	10.3 (39.1)
Steering pump cap. gpm (L/min)	5.8 (22)
Maximum total flow gpm (L/min)	16.1 (61.1)
Category, 3-point hitch	2
Hitch lift capacity, lb. (kg)	4270 (1937)
at 24 inches behind link ends, lb. (kg)	3153 (1430)
Lift control type	Position/Draft/Mech
Joystick valve	Yes
No. of standard remote valves-option	2

PTO

Type	Independent
Control	Electro-Hydraulic
Rear (rpm)	540/750/1000
Shaft diameter in. (mm)	1 3/8 (35)

CAPACITIES

Fuel tank, U.S. gal. (L)	18.48 (70)
Cooling system U.S. qt. (L)	10.6 (10)
Crankcase (with filter) U.S. qt. (L)	8.5 (8)
Trans. & hydr. system, U.S. gal. (L)	11 (42)
Front axle qt. (L)	17.4 (16.4)

DIMENSIONS (with standard tyres)

Overall length, in. (mm) with 3P	155.6 (3952)
Overall width, in. (mm)	72.4 (1840)
Wheelbase, in. (mm)	84.6 (2150)
Height to top of ROPS, in. (mm)	100.2 (2545)
Min. ground clearance, in. (mm)	17.1 (435)
Min. turning radius, in. (mm) with brakes	141.3 (3590)
Min. turning radius, in. (mm) w/o brakes	162.2 (4120)

STANDARD TYRES

Agricultural front	11.2-20
Agricultural rear	14.9-30
Industrial front	-
Industrial rear	-

ROLL-OVER PROTECTIVE STRUCTURES

Standard	CAB with air conditioner
----------	--------------------------

WEIGHT

Total weight, lb. (kg)	5555 (2520)
------------------------	-------------

