

CW Premium Series | Gasoline Belt Drive

Equipped with a heavy-duty belt drive system, the gas-driven CW Premium Series is deemed the workhorse of the Mi-T-M industrial pressure washer line.



CW-3504-5MGH

Pump

- Belt drive triplex piston General pump with ceramic plungers
- External bypass system allows more water into the system to protect from heat build-up
- Forged brass manifold (Nickel plated brass on 4000-PSI models)
- Thermal relief valve
- Water filter with clear sleeve for screen inspection
- Stainless-steel and brass unloader with preset pressure (3500 & 4000-PSI models have Mi-T-M unloader)

Frame

- Powder coated steel frame and base plate with 1 1/4-inch tube handles
- Flat-free tires
- Two-piece belt guard for quick access to belts

Engine

- Performance-proven engine with low-oil protection

Unit Includes

- Quick connect nozzles – 0°, 15°, 25° & 40°
- 50-foot x 3/8-inch non-marking hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip (48-inch on 3500 & 4000 PSI models)

CW Premium Series | Gasoline Belt Drive



| Model Number | PSI | GPM | Displacement/Engine | Pump | Unloader | Lance | Dimensions (LxWxH) | Ship Wt. | Net Wt. |
|--------------|------|-----|---|---------|-------------------------|-------|--------------------|----------|---------|
| CW-2505-4MGH | 2500 | 4.4 | 389cc Honda OHV | General | Preset pressure | 36in. | 45.5x28x26in. | 290 lb. | 216 lb. |
| CW-3004-4MGH | 3000 | 3.5 | 389cc Honda OHV | General | Preset pressure | 36in. | 45.5x28x26in. | 290 lb. | 216 lb. |
| CW-3504-5MGH | 3500 | 3.8 | 389cc Honda OHV | General | Mi-T-M, preset pressure | 48in. | 46x28x30in. | 290 lb. | 216 lb. |
| CW-3504-5MGS | 3500 | 3.8 | 404cc Subaru OHC | General | Mi-T-M, preset pressure | 48in. | 46x28x30in. | 290 lb. | 216 lb. |
| CW-4004-5MGH | 4000 | 3.5 | 389cc Honda OHV | General | Mi-T-M, preset pressure | 48in. | 46x28x30in. | 290 lb. | 216 lb. |
| CW-4004-5MVO | 4000 | 4.0 | 480cc Vanguard OHV, electric start (Battery included) | General | Mi-T-M, preset pressure | 48in. | 46x28x30in. | 330 lb. | 256 lb. |

Options:

| Part Number | Description | Fits Models |
|-------------|---|---------------------------------|
| CX-0005 | 48-in. insulated dual lance - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips | All models |
| CX-0045 | Electric start (Battery included) - For easy starting | 3000 to 4000-PSI Honda models |
| CX-0054 | Roll cage - Designed for cold water pressure washers to protect equipment, comes with a lifting hook, 1¼-in. powder coated steel tubing | All Honda models & CW-3504-5MGS |
| CX-0055 | Roll cage - Designed for cold water pressure washers to protect equipment, comes with a lifting hook, 1¼-in. powder coated steel tubing | CW-4004-5MVO |

Accessories:

| Part Number | Description | Fits Models |
|--------------|--|-------------|
| 50-0161 | High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up | All models |
| 851-0338 | 50-ft. x ¾-in. non-marking hose - For when you need extra hose for added mobility | All models |
| AW-8400-0021 | Low pressure detergent injector - Allows the user to apply the recommended detergents | All models |

