

LED Batten



LED T8 Batten Integrated



- Widely applied in factories, offices, banks, shopping centers, subways, schools and other places with high brightness and energy saving benefits
- For higher lumen applications, the LED tube can be replaced by 20W or 22W



Model	Voltage	Wattage	Color Temp	CRI (Ra)	Lumen	Dimension LxWxD (in.)
NL111E-18W/830	120V	18W	3000K	≥80	1400 lm	47.2 x 3.54 x 2.28
NL111E-18W/840	120V	18W	4000K	≥80	1450 lm	47.2 x 3.54 x 2.28
NL111E-18W/850	120V	18W	5000K	≥80	1500 lm	47.2 x 3.54 x 2.28
NL111E-18W/865	120V	18W	6500K	≥80	1550 lm	47.2 x 3.54 x 2.28
NL112E-18Wx2/830	120V	18Wx2	3000K	≥80	2750 lm	47.2 x 5.9 x 1.38
NL112E-18Wx2/840	120V	18Wx2	4000K	≥80	2800 lm	47.2 x 5.9 x 1.38
NL112E-18Wx2/850	120V	18Wx2	5000K	≥80	2850 lm	47.2 x 5.9 x 1.38
NL112E-18Wx2/865	120V	18Wx2	6500K	≥80	2900 lm	47.2 x 5.9 x 1.38