

## EV-FLEX™ Electric Vehicle Level 2 Charging Station

Meet the best-in-class EV charging network technology for at home or on the go. The EV-FLEX™ Level 2 charging station is the ideal EV charging solution for multi-tenant residential, commercial, retail or municipal properties.

Flexibly Mounted on a Wall, Ceiling, Pole or Pedestal | WiFi & LTE Cellular Enabled for Public or Private networks | RFID, Smartphone App and Bluetooth User Authentication | Real-Time Load Management and Demand Response | Tamper Resistant; Rated for Indoor/Outdoor use | Universal Compatibility



## EV-FLEX LITE™ Electric Vehicle Level 2 Charging Station

The EV-FLEX LITE™ Level 2 charging station is the ideal EV charging solution for single family or multi tenant residential/light commercial properties.

Flexibly Mounted On a Wall, Ceiling, Pole or Pedestal | WiFi Enabled for Public or Private Networks | Smartphone App User Authentication | Real-Time Load Management and Demand Response | Tamper Resistant; Rated for Indoor/Outdoor use Universal Compatibility



## EV-FLEET™ Electric Vehicle Level 2 Charging Station

The EV-FLEET™ Level 2 charging station is the ideal EV charging solution for medium to heavy duty applications.

Up to 2.5x Faster Than Standard Level 2 Chargers | Flexibly Mounted On a Wall, Ceiling, Pole or Pedestal | WiFi & LTE Cellular Enabled for Public or Private networks | RFID, Smartphone App and Bluetooth user authentication | Real-Time Load Management and Demand Response | Tamper Resistant; Rated for Indoor/Outdoor use Universal Compatibility



## EV-FAST™ Electric Vehicle DC Fast Charging Station

The EV-FAST™ DC fast charging station is the ideal EV charging solution for commercial, retail or public-access properties.

Direct Current (DC) Fast Charging | Reduced Installation Time & Cost | Liquid Cooling Technology OCCP 1.5 and 1.6 Compliant UL Listed & CALeVIP Approved | Power: 50/75 kW max | Up to 920V & 188A | Universal Compatibility



## LOOP NETWORK ROUTER

An optional expansion hardware for increasing network communication range where signal strength is poor. Loop Network Router has industry leading technical specifications.

Dual Modem Capable | Embedded 150M-D Modem | Two LAN/WAN switchable Ethernet ports (one 10/100/1000 and one 10/100) - one default WAN | 2x2 MIMO "N" 2.4 GHz WiFi: 802.11 b/g/n (IBR600C only) | Serial console support for Out-of-Band Management of a connected device.



## LOOP CHARGING STATION PEDESTAL

Single or Dual mount option. Dual manhole design to make it more contractor friendly when terminating wires. Sleek and compact design works solely with the Loop Level 2 Charging Stations.

ADA Compliant | Only 20 lbs | Dimensions: 52.8" x 6" x 2"  
Powder Coated Extruded Aluminum | Water Resistant

