CWC Premium Series | Gasoline Belt Drive

The CWC Series features a 1¹/₄-inch roll cage, handle and lifting hook, making this pressure washer one of the most powerful on the market today.



Pump

- Belt drive triplex piston AR or General pump with ceramic plungers
- External bypass system allows more water into the system to protect from heat build-up
- Forged brass manifold
- Thermal and safety relief valves
- Water filter with clear sleeve for screen inspection (High capacity water filter on CWC-3008-4MGH)
- Stainless-steel and brass unloader with preset pressure

Frame

- Powder coated steel frame with 1¼-inch roll cage, handles and lifting hook
- Flat-free tires and locking brake

Engine

- Performace-proven engine with low-oil protection

Components

- Fuel tank is powder coated outside and aluminized steel inside to prevent rusting

CWC-5004-4MAH

- 13-gallon fuel tank capacity for 91/2 hour run time

Unit Includes:

- Quick connect nozzles 0°, 15°, 25° & 40°
- 50-foot x %-inch high pressure hose with quick connects, swivel and bend restrictors (CWC-5000 models have non-marking hose) (CWC-6004 & CWC-7004 have a black hose)
- 50-foot x ½-inch high pressure black hose with quick connects (CWC-3008-4MGH)
- Professional-grade insulated trigger gun with safety lock-off
- 48-inch lance with rubber grip

CWC Premium Series | Gasoline Belt Drive



Model Number	PSI	GPM	Displacement/Engine	Pump	Unloader	Lance	Dimensions (LxWxH)	Ship Wt.	Net Wt.
CWC-3008-4MGH	3000	8.0	688cc Honda OHV, electric start (Battery included)	General	Preset pressure	48in.	43x27.75x36in.	531 lb.	408 lb.
CWC-5004-4MAH	5000	4.0	688cc Honda OHV, electric start (Battery included)	AR	Preset pressure	48in.	43x27.75x36in.	521 lb.	398 lb.
CWC-5004-4MGH	5000	4.0	688cc Honda OHV, electric start (Battery included)	General	Preset pressure	48in.	43x27.75x36in.	521 lb.	398 lb.
CWC-5005-4MGH	5000	5.0	688cc Honda OHV, electric start (Battery included)	General	Preset pressure	48in.	43x27.75x36in.	531 lb.	408 lb.
CWC-6004-4MGH	6000	3.7	688cc Honda OHV, electric start (Battery included)	General	Preset pressure	48in.	43x27.75x36in.	531 lb.	408 lb.
CWC-7004-4MGH	7000	3.8	688cc Honda OHV, electric start (Battery included)	General	Preset pressure	48in.	43.25x28.5x39.25in.	515 lb.	398 lb.

Accessories:						
Part Number	Description	Fits Models				
851-0089	50-ft. x 1/2-in. high pressure hose - For when you need extra hose for added mobility	CWC-3008-4MGH				
851-0317	50-ft. x %-in. non-marking hose - For when you need extra hose for added mobility	CWC-5004 & CWC-5005 models				
851-0362	50-ft. x %-in. high pressure hose - For when you need extra hose for added mobility	CWC-6004-4MGH				
AW-3000-0035	Sand injector - Remove coatings from steel and concrete surfaces	CWC-5004 & CWC-6004 models				
AW-7500-0035	Rotating nozzle - Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage	CWC-5004 & CWC-6004 models				

