



CARPENTER

We bring comfort to your life.™

Material Information Data Sheet

Polyurethane - flexible foam

Issue date: 6th June 2013

Material: Polyurethane flexible foam or PUR

Manufacturer: Carpenter Ltd

Address: Dinting Lodge Industrial Estate, Glossop, Derbyshire. SK13 6LE

Tel/fax: +44(0)1457 861141 / +44(0)1457 863242

E-Mail: sales.uk@carpenter.com

Polyurethane foams are not considered to be hazardous products nor as mixtures of dangerous substances. They are identified as industrial polymers. According to EU Regulation 1907/2006EC (REACH) Polyurethane foams are defined as “articles”.

A. Product Identification

Product names: Polyether Polyurethane Foam
Polyester Polyurethane Foam

Trade names: Various, depending on the manufacturer

Composition: Polyurethane polymer

Chemical description: Poly-addition product of isocyanates, polyether/
polyester polyols and water, controlled by
catalysts, stabilizers and other additives,



CARPENTER

We bring comfort to your life.™

resulting in a cellular polyurethane foam

Regulatory Information

No labeling is currently required for this material by existing EU Regulation on Classification, Packaging and Labeling of substances and mixtures (1272/2008/EC)

B. Physical properties

Physical form/appearance:

Cellular material with elastic properties

Colour:

Varies according to manufacturer's choice

Specific gravity:

10-300 kg/m³

Solubility in water:

Insoluble

Odour:

None or mild odour

Flash ignition point:

Between 315°C to 370°C

Decomposition temperature:

Above 180°C

Thermal energy:

28.000 KJ/kg

Stability and reactivity:

The product is stable at temperatures between - 40°C and + 100°C

C. Fire Hazards

Auto-ignition point :
(ASTM D 1929)

Between 370°C to 427°C



CARPENTER

We bring comfort to your life.™

Fire hazard:	The product is a combustible material and causes, when burning, intense heat and dense smoke. In a fire, decomposition products such as carbon black, carbon monoxide, carbon dioxide, gaseous hydrocarbons and nitrogen containing products can be generated in various concentrations depending on the combustion conditions.
Melting point:	The product has no melting point but will decompose into gaseous components
Suitable fire extinguishers:	Water, carbon dioxide, dry powder, liquid foam.
Human protection in large fires:	Fire fighters should use self-contained breathing apparatus. Should the burning foam come in contact with skin, cool the burned area with water without removing the foam. In case of serious burns call a doctor immediately. In the event of persons inhaling combustion gases, they must be removed from the area and given swift medical attention.
Further fire information:	Terms like “is flame retarded” or “contains flame retardants” are sometimes used to describe improved ignition resistance in small-scale tests and do not reflect hazards in large scale fire conditions.
Storage & Processing:	In processing flexible PU Foams all prescriptions, directives and technical rules regarding the layout of workstations, machinery safety and workplace human protection must be observed. Because of the fire risks associated with certain processing operations on block foam (e.g. hot-wire cutting, crumbing, flame lamination, etc) it is advisable to seek expert guidance on fire precautions that need to be in place. Attention should be paid to the possibility to produce electrostatic charges during foam processing operations that may be dangerous.



CARPENTER

We bring comfort to your life.™

D. Toxicological data

Oral:	There is no evidence that PU foam is toxic in case of ingestion. LD50 (oral-rats) >5000 mg/kg.
Inhalation:	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg/m ³ 8-hour TWA of inhalable dust or 4 mg/m ³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels.
Skin contact:	No adverse effects known following contact with PU foam.
Eye contact:	Dust particles can cause mechanical irritation. Rinse with water to remove dust.
Microbiological: contamination:	PU foam is sterile when manufactured.

E. Protective measures in handling, storage and processing

	Special protective equipment and clothing is not necessary when handling foam, since it does not irritate the skin, eyes or respiratory system, except in those processes where dust is produced.
Ventilation:	Provided there is adequate general ventilation, no special precautions are necessary for most handling and cutting operations.



CARPENTER

We bring comfort to your life.™

Ventilation during some operations: Local exhaust ventilation is necessary for some operations i.e. where dust is produced from sawing, buffing or crumbing operations or where fumes are produced in flame laminating, thermoforming or hot wire cutting.

Storage: Store away from heat sources (match, cigarette, open fire, electrical heater, ...). UV rays may cause surface discoloration. This does not affect the physical properties of the foam. Store in compliance with safety standards established by local Authorities and by specific requirements of the Insurance Companies

Eye protection: Protective goggles should be worn for processes which generate dust.

Protective clothing: Not required. In case of dust generating operations skin protective clothes and appropriate respiratory masks are recommended

Other measures: No specific measures are needed for fully cured PUR foam. Gloves should be used when handling fresh foams.

F. Ecological information

Biodegradability: Dependent on the type of PU foam, the product is not degradable or degrades slowly.

Additional ecological data: In case of a standard foam fire, the particles that fall in the water are harmless. They are sieved



CARPENTER

We bring comfort to your life.™

out of the water and/or disintegrated in the water treatment plant. Living organisms in the water are not endangered.

PU Flexible Foams do not contain Ozone depleting substances and are not produced using products regulated by pertinent Legislation

G. Transport information

Labeling:

PU foam is not classified for conveyance or supply under the International Agreements on Carriage of Dangerous Goods. The product is not classified as hazardous for any mode of transportation under current EU/UN regulations.

Measures:

No special steps need to be taken for the transportation of PU foam.

H. Disposal considerations

Production trim:

Trim polyurethane foam and off-cuts can usually be recycled by several methods, provided they are clean and sorted.

Post Consumer Waste:

A major recycling option exists via rebonding if a series of technical and economic conditions are met. If recycling is not possible, scrap or post-consumer PU foam waste can be used for energy recovery or be disposed of at licensed landfill sites or by incineration under controlled conditions in agreement with EU and National regulatory provisions and following advice from the Local Waste Regulation Authority.



CARPENTER

We bring comfort to your life.™

Legislation:

Under EU environmental legislation, there are no special requirements for the disposal of conventional PU foam.

I. Disclaimer of liability

The local legislation is to be followed.

This information is furnished without warranty, expressed or implied, except that it is accurate according to the best available knowledge of the PU foam manufacturer.

The data on this sheet relate only to the specific material designated herein.

The manufacturer assumes no legal responsibility for use of, or reliance upon these data. For information regarding specific applications of the product, the foam manufacturer should be contacted.



CARPENTER

We bring comfort to your life.™

Input for external Material Data Systems or PU foam convertors.

Flexible polyurethanes are polymers and defined in Data Systems, i.e. IMDS, as a product, not as a chemical compound. In terms of REACH polyurethane foam is defined as article.

For the manufacture of PU foam, a series of raw materials are used. These include isocyanates, polyols (major proportion) and water (small proportion). These ingredients are fully reacted during foam manufacture and chemically converted into the PU polymer matrix. In addition, other essential additives of different characteristics are used in small concentrations, some of which could be also chemically bonded to the matrix.

Depending on the final application, legal requirements or customer's request PU foam may contain any of the following substances:

- Aliphatic and/or cycloaliphatic amine catalysts
- Flame-retardants
- Plasticisers
- Silicone and/or organic surfactants
- Inorganic Tin catalysts
- Organic and/or inorganic pigments.

No detailed breakdown of the finished foam in any of these raw materials or additives can be expressed as final percentages, as most are reactive and chemically bonded to the PU foam matrix or disappear gradually during the curing phase (24h) of the manufacture.

Additives, which prohibit the rebonding recycling route, are not present.

Substances like Hg, Cd, Pb and Cr6+ are not intentionally added to the formulation. When reporting to customers in the automotive sector the use of IMDS is required. Besides the material PU Foam, additives are to be reported according to the requirements of GADSL (Global Automotive Declarable Substance List).