



TYM T293
WITH TURF TYRES

Product image shown for illustration only

T293 HST

SUPERB RANGE, UNBEATABLE VALUE

The TYM compact tractor range. Powerful, reliable, four-cylinder diesel engines available from 25 to 105hp mean these superb workhorses can cover a wide variety of groundscape tasks while offering unbeatable value for money.

Packed full of innovative features such as easy-to-read LED display, hydrostatic power-steering, optional weather cab, and much more, TYM tractors make the ideal choice for any discerning greenkeeper, groundsman, contractor or landscaper. Some models available with heated and air conditioned cabs, power shuttle and hydrostatic transmissions. While all models can be fitted with optional loaders and backhoes.

**FREE ONSITE
DEMONSTRATION**
CALL TODAY

Put us to the test. For a free onsite demonstration, call Reesink Turfcare on 01480 226800.



T525



T293



T353



T640



T393



T433



T503



T654



T754



T1004

MODEL

ENGINE

Manufacturer	Mitsubishi
Model	S3L2
Engine HP (kw)-gross	29 (21.3)
PTO HP (kw)	21.8 (16.4)
Rated engine speed	2800
Number of cylinders	3
Displacement-cu.in. (cc)	80.4 (1318)
Air cleaner	Dual Dry

ELECTRICAL SYSTEM

Alternator	12V, 50A
------------	----------

FUEL SYSTEM

Type	Indirect fuel injection
------	-------------------------

DRIVETRAIN

Transmission type	HST
Number of speeds	Infinite / 2 Range
Max travelling speed, mph (km/h)	14.9 (24)
Brakes	Wet disc
Steering	Hydrostatic
Clutch	N/A

HYDRAULIC SYSTEM

Pump (type)	Dual gear pump
Implement pump cap. gpm (L/min)	5.2 (19.6)
Steering pump cap. gpm (L/min)	2.7 (10.4)
Maximum total flow gpm (L/min)	7.8 (29.6)
Category, 3-point hitch	I
Hitch lift capacity, lb. (kg)	1534 (700)
at 24 inches behind link ends, lb. (kg)	1102 (500)
Lift control type	Position
Joystick valve	Standard
No. of standard remote valves-option	1

PTO

Type	Independent
Control	Electric/Hydro
Mid (rpm) option	2000
Rear (rpm)	540
Shaft diameter in. (mm)	1 3/8 (35)

CAPACITIES

Fuel tank, U.S. gal. (L)	6.6 (25)
Cooling system U.S. qt. (L)	5.9 (5.6)
Crankcase (with filter) U.S. qt. (L)	4.5 (4.3)
Trans. & hydr. system, U.S. gal. (L)	5.8 (17)
Front axle qt. (L)	4.7 (4.5)

DIMENSIONS (with standard tyres)

Overall length, in. (mm) with 3P	107.8 (2740)
Overall width, in. (mm)	56.3 (1430)
Wheelbase, in. (mm)	58.3 (1480)
Height to top of ROPS, in. (mm)	91.7 (2330)
Min. ground clearance, in. (mm)	9.8 (250)
Min. turning radius, in. (mm) with brakes	96.2 (2442)
Min. turning radius, in. (mm) w/o brakes	102.8 (2612)

STANDARD TYRES

Agricultural front	-
Agricultural rear	-
Industrial front	25x8.5-14
Industrial rear	14-17.5

ROLL-OVER PROTECTIVE STRUCTURES

Standard	ROPS
----------	------

WEIGHT

Total weight, lb. (kg)	1980 (898)
------------------------	------------

