# **Two Stage Gasoline**

Ideal for both contractors and remodelers this two stage air compressor provides a reliable air source on remote jobsites. This model allows for more air to be stored for future use while generating less heat which reduces wear and extends the life of the air compressor.

8-Gallon



- Stainless-steel braided discharge hose
- Large canister intake filter

### **Engine**

- Industrial Honda OHV, Kohler OHV or Subaru OHC engine
- Pneumatic idle control to conserve fuel
- Engine oil drain

#### Frame

- Powder coated 8-gallon twin tank receivers
- 3/16-inch base plate to reduce vibration
- 14-gauge powder coated two-piece belt guard with 1/4-turn release for quick access to belts
- Convenient lifting handles
- Two pneumatic tires with tubes and steel hubs
- Heavy-duty axle

#### Components

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- Belt tightening system pulls engine straight to ensure constant belt alignment
- 16.5-inch fly wheel for extra cooling and longer life
- Quality pilot valve unloader

#### Warranties







## **NEW KOHLER ENGINE MODEL**

<b>Model Number</b>	CFM @ PSI	Displacement/Engine	Dimensions (LxWxH)	Ship Wt.	Net Wt.
AM2-PH09-08M	17.2 @ 175	270cc Honda OHV	44in.x26in.x31in.	330 lbs.	260 lbs.
AM2-PK95-08M	17.2 @ 175	277cc Kohler OHV	44in.x26in.x31in.	330 lbs.	260 lbs.
AM2-PR09-08M	17.2 @ 175	265cc Subaru OHC	44in.x26in.x31in.	330 lbs.	260 lbs.

#### OPTIONS

Part Number	Description	Fits Models
AX-0003	Manual drain metal bowl - Drains moisture from air system	All models
AX-0015	Electric start (battery and cables not included) - For easy starting	AM2-PH09-08M
AX-0041	Electric start (battery and cables not included) - For easy starting	AM2-PR09-08M
<b>Consult Factory</b>	Cable throttle control - Automatically throttles down engine to conserve fuel	Honda & Subaru models
TX-1002-W	Puncture-proof tires - Tires are flat-free, maintenance-free, 10-inch, white hub, two tires	All models