

# 260P

## **DESCRIPTION:**

BCS 260P is a non-chelated, non-caustic, liquid spray wash cleaner with a blend of alkaline builders, water conditioners, low foaming surfactants and short-term corrosion inhibitors. BCS 260-PNC is suitable for ferrous and non-ferrous metals and can be used at temperatures from 80°F to 160°F.

## **ADVANTAGES:**

- Multi-metal Safe
- Can be used in hard water areas
- Short term in-process rust protection
- Low Foaming
- Easy handling Liquid
- Contains no Phosphates

## **TYPICAL APPLICATION:**

The unique formulation of BCS 260P allows its use in more than one application.

*Primary Use:* Spray Wash Cleaner

*Aluminum Safe:* Hot Tank Cleaner

## **USE INSTRUCTIONS:**

**Spray Wash** 0.5% to 5% by volume, depending on soils. Use at temperatures ranging from 80°F to 160°F. If no history of cleaning is available, start the cleaning process at a high percentage of cleaner and a high temperature. Reduce each part until the best results are seen at the most economical concentration and temperature.

**Hot Tank** 3% to 8% by volume, depending on soils. Use at temperatures ranging from 140°F to 160°F. Agitation of tank will improve cleaning results and cleaning time.

For additional information such as physical characteristics, safety precautions, disposal, etc., see corresponding SDS.