



## POSI LOCK ALIGNMENT ACCESSORIES

Demo video can be found here: <http://www.ctrline.net/demo-videos.html>

### SIDE ALIGN TOOL KITS

All-in-one, go-anywhere portable jack bolt sets. Aligning rotating machinery is not just about precision measuring, but also precision adjustments. Use the smooth power of an eccentric socket to turn rotary motion into controlled linear movement. By rotating the eccentric socket, linear movement is transferred to the motor foot, creating a precise movement to the desired alignment position. Available in standard or metric sizes for machines 2 to 300HP. Kits include carrying case. Individual components also available.



**Part Number: AT-1104**  
**\$ 800.00**

Kit includes the following actuator socket sizes:  
 (for in between sizes, use the next size up)

Size	Tool Range
9/16"	13/16 to 1-5/8 in.
3/4"	7/8 to 2 in.
15/16"	7/8 to 2-5/8 in.
1-1/8"	7/8 to 2-5/8 in.



**Part Number: AT-1108**  
**\$ 1,360.00**

Same as AT-1104 plus the following additional actuator socket sizes:  
 (for in between sizes, use the next size up)

Size	Tool Range
1-5/16"	1-1/2 to 4-1/2 in.
1-1/2"	1-1/2 to 4-1/2 in.
1-11/16"	1-7/8 to 6-1/8 in.
1-7/8"	1-7/8 to 6-1/8 in.

### UNDERCUT BOLT KITS

Posi Lock's undercut bolt sets virtually eliminate the problem of 'bolt-binding'. This innovative precision undercut bolt and washer system helps you achieve and maintain perfect alignment faster and easier than ever before. The sets feature hardened, grade-8 bolts with maximum clearance and through-hardened, plated washers. Kits include carrying case. Individual components also available.

**Part Number: UB200 \$1,070.00**



UB200 Kit includes the following:

24 ea. 5/16" Bolts with washers  
 (12 ea. of lengths 1-1/4" and 1-1/2")

24 ea. 3/8" Bolts with washers  
 (12 ea. of lengths 1-1/4" and 1-1/2")

36 ea. 1/2" Bolts with washers  
 (12 ea. of lengths 1-1/2", 1-3/4" and 2")



**Part Number: UB300 \$1,730.00**



UB300 Kit includes the following:

36 ea. 9/16" Bolts with washers  
 (12 ea. of lengths 1-1/2", 2" and 2-1/2")

36 ea. 5/8" Bolts with washers  
 (12 ea. of lengths 2", 2-1/4" and 2-1/2")

36 ea. 3/4" Bolts with washers  
 (12 ea. of lengths 2", 2-1/4" and 2-1/2")