



TYM TS25/TX25
WITH INDUSTRIAL TYRES

Product image shown for illustration only

TS25

SUPERB RANGE, UNBEATABLE VALUE

The TYM compact tractor range. Powerful, reliable, four-cylinder diesel engines available from 25 to 105hp mean these superb workhorses can cover a wide variety of groundscape tasks while offering unbeatable value for money.

Packed full of innovative features such as easy-to-read LED display, hydrostatic power-steering, optional weather cab, and much more, TYM tractors make the ideal choice for any discerning greenkeeper, groundsman, contractor or landscaper. Some models available with heated and air conditioned cabs, power shuttle and hydrostatic transmissions. While all models can be fitted with optional loaders and backhoes.

**FREE ONSITE
DEMONSTRATION**
CALL TODAY

Put us to the test. For a free onsite demonstration, call Reesink Turfcare on 01480 226800.



TS25



T293



T353



TE40



T393



T433



T503



T654



T754



T1004

MODEL

ENGINE

Manufacturer
Model
Engine HP (kw)-gross
PTO HP (kw)
Rated engine speed
Number of cylinders
Displacement-cu.in. (cc)
Air cleaner

ELECTRICAL SYSTEM

Alternator

FUEL SYSTEM

Type

DRIVETRAIN

Transmission type
Number of speeds
Max travelling speed, mph (km/h)
Brakes
Steering
Clutch

HYDRAULIC SYSTEM

Pump (type)
Implement pump cap. gpm (L/min)
Steering pump cap. gpm (L/min)
Maximum total flow gpm (L/min)
Category, 3-point hitch
Hitch lift capacity, lb. (kg)
at 24 inches behind link ends, lb. (kg)
Lift control type
Joystick valve
No. of standard remote valves-option

PTO

Type
Control
Mid (rpm) option
Rear (rpm)
Shaft diameter in. (mm)

CAPACITIES

Fuel tank, U.S. gal. (L)
Cooling system U.S. qt. (L)
Crankcase (with filter) U.S. qt. (L)
Trans. & hydr. system, U.S. gal. (L)
Front axle qt. (L)

DIMENSIONS (with standard tyres)

Overall length, in. (mm) with 3P
Overall width, in. (mm)
Wheelbase, in. (mm)
Height to top of ROPS, in. (mm)
Min. ground clearance, in. (mm)
Min. turning radius, in. (mm) with brakes
Min. turning radius, in. (mm) w/o brakes

STANDARD TYRES

Agricultural front
Agricultural rear
Industrial front
Industrial rear

ROLL-OVER PROTECTIVE STRUCTURES

Standard

WEIGHT

Total weight, lb. (kg)

TS25NC

Yanmar
3TNV76
25 (19.3)
21.4 (16.2)
3000
3
1116
Single element

12V, 40A

Indirect fuel injection

Manual
6F x 2 Range
11 (17.7)
Wet disc
Hydrostatic
N/A

Dual gear pump
4.18 (15.8)
2.77 (10.5)
6.95 (26.3)
1
1322 (600)
1058 (480)
Position
W/ Loader
Optional

Mechanical
Hydro
2000
540
1 3/8 (35)

5.81 (22)
3.8 (3.6)
2.9 (2.7)
3.7 (14)
3.7 (3.5)

105 (2668)
45.8 (1164)
57.4 (1460)
10.2 (260)
9.4 (240)
89.4 (2.22)
100 (2.54)

6-12
9.5-16
20x8-10
27x12.5-15

ROPS

1893 (768)

TS25NH

Yanmar
3TNV76
25 (19.3)
21.4 (16.2)
3000
3
1116
Single element

12V, 40A

Indirect fuel injection

HST
Infinite / 2 Range
11.2 (18.1)
Wet disc
Hydrostatic
N/A

Dual gear pump
4.18 (15.8)
2.77 (10.5)
6.95 (26.3)
1
1322 (600)
1058 (480)
Position
W/ Loader
Optional

Electric switch
Hydro
2000
540
1 3/8 (35)

5.81 (22)
3.8 (3.6)
2.9 (2.7)
3.7 (14)
3.7 (3.5)

105 (2668)
45.8 (1164)
57.4 (1460)
10.2 (260)
9.4 (240)
~
100 (2.54)

6-12
9.5-16
20x8-10
27x12.5-15

ROPS

1667 (756)

