

CW Premium Series | Electric Belt Drive Stationary

Stationary yet versatile, the electric CW Series is the ideal model for wash bays, golf courses and restaurant applications. The stainless-steel base and frame ensures longevity in the toughest environments.



CW-2004-SME1
(Shown with standard low pressure detergent injector)

Pump

- Belt drive triplex piston General pump with ceramic plungers
- Forged brass manifold
- Thermal relief valve
- Pump accepts incoming water up to 175°F
- Quick connect low pressure detergent injector
- Stainless-steel and brass unloader with preset pressure

Motor

- Totally enclosed fan-cooled electric motor with manual thermal overload protection (2000-PSI models)
- Open drip-proof electric motor (1000 & 3000-PSI models)

Frame

- Stainless-steel base and frame with removable panels

Component

- Time delay shutdown

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° & 40°
- 50-foot x 3/8-inch high pressure black hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance

CW Premium Series | Electric Belt Drive Stationary



NEMA 5-20P,
20-amp plug



NEMA L15-20P,
20-amp plug



NEMA L15-30P,
30-amp plug



NEMA 6-30P,
30-amp plug



Model Number	PSI	GPM	Horsepower/Motor	Pump	Unloader	Plug Type	Lance	Dimensions (LxWxH)	Ship Wt.	Net Wt.
CW-1003-SME1	1000	2.5	2.0 HP, 120V, 1Ø, 18.8A	General	Factory preset	NEMA 5-20P	Adjustable, dual	29.5x20.5x15in.	222 lb.	172 lb.
CW-2004-SME1	2000	3.9	6.0 HP, 230V, 1Ø, 22.0A	General	Factory preset	NEMA 6-30P	Adjustable, dual	29.5x20.5x15in.	272 lb.	214 lb.
CW-2004-SME3*	2000	3.9	6.0 HP, 230V, 3Ø, 15.0A	General	Factory preset	NEMA L15-20P	Adjustable, dual	29.5x20.5x15in.	262 lb.	204 lb.
CW-3004-SME3*	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A	General	Factory preset	NEMA L15-30P	Adjustable, dual	29.5x20.5x15in.	292 lb.	234 lb.

*460V motors available as options.

Options:

Part Number	Description	Fits Models
CX-0069	Auto start/stop - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	All models
CX-0076	460V on 6.0-HP, 3-phase model - For when you have 460V of power available	CW-2004-SME3
CX-0077	460V on 8.0-HP, 3-phase model - For when you have 460V of power available	CW-3004-SME3
CX-0078	Remote box - Adds control box which may be mounted away from unit to control on/off	All models
CX-0096	Hour meter - Displays the number of hours unit has been in operation	All models

Accessories:

Part Number	Description	Fits Models
AW-9501-0000	Stainless-steel wall mounting bracket - Provides a permanent location for your pressure washer in a shop or plant facility	All models
AW-9502-0000	Powder coated steel wall mounting bracket - Provides a permanent location for your pressure washer in a shop or plant facility	All models
AW-9502-0001	Powder coated steel floor stand - Provides a permanent location for your pressure washer in a shop or plant facility	All models

