


LED Tubular Lamp

LED T8 INSTAlite Glass (UL Type A)



- Energy saving up to 46% compare to F32T8 system
- Perfect retrofit traditional lamps for INSTANT START circuit
- 280° beam angle allows fixture to maintain original light distribution by parabolic reflector
- Smooth operation even at low temperatures down to -20°C
- No mercury and hazardous substances
- Compatible with most common instant start electronic ballasts (Refer to the ballast compatibility list)
- No re-wiring cost
- Ra90 available on request
- Full glass body with safety approval
- * DLC certified



Model	Wattage	Color	Color Temp	CRI (Ra)	Lumen	Beam Angle	Length MOL (in.)
LED F8T8/830/G/NA/IS	8W	Warm White	3000K	≥80	950 lm	280°	24
LED F8T8/835/G/NA/IS	8W	White	3500K	≥80	950 lm	280°	24
LED F8T8/840/G/NA/IS	8W	Neutral White	4000K	≥80	1000 lm	280°	24
LED F8T8/850/G/NA/IS	8W	Cool White	5000K	≥80	1050 lm	280°	24
LED F11T8/830/G/NA/IS	11W	Warm White	3000K	≥80	1100 lm	280°	36
LED F11T8/835/G/NA/IS	11W	White	3500K	≥80	1100 lm	280°	36
LED F11T8/840/G/NA/IS	11W	Neutral White	4000K	≥80	1150 lm	280°	36
LED F11T8/850/G/NA/IS	11W	Cool White	5000K	≥80	1200 lm	280°	36
* LED F15T8/830/G/NA/IS	15W	Warm White	3000K	≥80	1500 lm	280°	48
* LED F15T8/835/G/NA/IS	15W	White	3500K	≥80	1500 lm	280°	48
* LED F15T8/840/G/NA/IS	15W	Neutral White	4000K	≥80	1600 lm	280°	48
* LED F15T8/850/G/NA/IS	15W	Cool White	5000K	≥80	1650 lm	280°	48
* LED F17T8/830/G/NA/IS	17W	Warm White	3000K	≥80	2000 lm	280°	48
* LED F17T8/835/G/NA/IS	17W	White	3500K	≥80	2000 lm	280°	48
* LED F17T8/840/G/NA/IS	17W	Neutral White	4000K	≥80	2050 lm	280°	48
* LED F17T8/850/G/NA/IS	17W	Cool White	5000K	≥80	2100 lm	280°	48
LED F21T8/830/G/NA/IS	21W	Warm White	3000K	≥80	2100 lm	280°	60
LED F21T8/835/G/NA/IS	21W	White	3500K	≥80	2100 lm	280°	60
LED F21T8/840/G/NA/IS	21W	Neutral White	4000K	≥80	2210 lm	280°	60
LED F21T8/850/G/NA/IS	21W	Cool White	5000K	≥80	2290 lm	280°	60