

LED Batten



LED T8 Batten Replaceable



- Widely applied in factories, offices, banks, shopping centers, subways, schools and other places with high brightness and energy saving benefits
- For higher lumen applications , the LED tube can be replaced by 20W or 22W
- Tubes can be replaceable by UL Type B LED tubes
- Model suggestion: AC Instant, Universal NA & Global Pro



Model	Voltage	Wattage	Color Temp	CRI (Ra)	Lumen	Dimension LxWxD (in.)
NL121A-18W/830	120V	18W	3000K	≥80	1450 lm	48 x 1.57 x 2.2
NL121A-18W/840	120V	18W	4000K	≥80	1500 lm	48 x 1.57 x 2.2
NL121A-18W/850	120V	18W	5000K	≥80	1550 lm	48 x 1.57 x 2.2
NL121A-18W/865	120V	18W	6500K	≥80	1600 lm	48 x 1.57 x 2.2
NL122A-18Wx2/830	120V	18Wx2	3000K	≥80	2800 lm	48 x 3.15 x 2.2
NL122A-18Wx2/840	120V	18Wx2	4000K	≥80	2850 lm	48 x 3.15 x 2.2
NL122A-18Wx2/850	120V	18Wx2	5000K	≥80	2900 lm	48 x 3.15 x 2.2
NL122A-18Wx2/865	120V	18Wx2	6500K	≥80	2980 lm	48 x 3.15 x 2.2