LED Striplight Tunable White

EMITTER ENERGY INC.

Features
· Extremely energy saving with low power consumption
· High brightness, multi-functional for linear decoration
· Long average life 30000 hours
· Selective CCT From 2300K to 6500K
· Low thermal output with no IR and harmful UV
· No mercury and hazardous substances
· For all strips with wattage over 14.4W, an aluminium profile
  must be used
· Dimmable as option
· Color Rendering Index: ≥90

Materials / Finish
· Chips : SMD 2016

Installation / Mounting
· Easy to install with 3M adhensive tape, mounting brackets and profile

Standards
· Class III Electrical
· IP20, IP54, IP65, IP67
· UL, ETL

* Package Content : - 5m per reel

LED Driver Controllers

12V/24V
LED Driver

LED CCT
Controller

LED Touch CCT
Controller

LED Remote CCT
Dimming Controller

Connectors

4 Pin
Quick Connector

Strip-to-Wire

Strip-to-Strip

'I' Type
Fast Plug

'T' Type
Fast Plug

Wire-to-Wire
Fast Plug

Profiles

8   12.2
     17

Surface
mounted

Recessed

8   12.2
     17

Unit in mm
* Extra profiles and accessories need to order separately.

IP Structures

1   LED
     PCB
10
IP20

2.2   LED
       SI Glue
       PCB
10
IP54-S

4   LED
     SI Tube
     PCB
12
IP65

4.8   LED
       SI
       PCB
12
IP67-R

30,000h | SMD | | | IP20 | IP54 | IP65 | IP67 | NO UV | No INFRA RED | | UL LISTED | ETL

Model	Voltage	Wattage	Color Temp	Lumen	PCB Width	Cutting Unit (12V / 24V)	No. of LEDs
LED 2016 9.6W 10-120 TW	9.6W/m	12V / 24V DC	2300-6500K	960lm/m	10mm	50mm/6LEDs / 100mm/12LEDs	120 pcs/m
LED 2016 19.2W 10-240 TW	19.2W/m	24V DC	2300-6500K	1920lm/m	10mm	50mm/12LEDs	240 pcs/m