

# Stucco Systems Warranties and Requirements

TECHNICAL BULLETIN  
1025473

Senergy® offers a package of progressive warranty options for various stucco wall systems commensurate with product and system upgrades. The information provided here summarizes the warranties we offer. For additional assistance in evaluating the systems, please refer to Senergy's Choose Your Stucco brochure, visit the Senergy web site at [www.senergy.cc](http://www.senergy.cc), call the BASF Wall Systems Technical Department at 1-800-589-1336 or contact your local Senergy distributor.

## Senergy Stucco System Warranties

SENERGY STUCCOBASE™ applied per specification of 3/8" to 1/2" thick with (optional) PermaLath™ or 3/4" to 7/8" thick stuccobase with (optional) PermaLath™ 1000, and finished with one of the following options:

- A. SENERFLEX® Finish, 100% acrylic polymer-based finish—3-year limited material & labor warranty
- B. SILCOAT™ Finish, silicone-enhanced 100% acrylic polymer-based finish—3-year limited material & labor warranty
- C. SENERLASTIC™ Finish, 100% acrylic polymer-based elastomeric finish—5-year limited material & labor warranty
- D. SENERLASTIC™ PLUS Finish, siliconized elastomeric finish—7-year limited material & labor warranty

## Senergy Premium Stucco Systems Warranties

The project must be greater than 10,000 square feet of stucco wall area. Plan review and final inspection required.

SENERGY STUCCOBASE applied per specification of 3/8" to 1/2" thick with (optional) PermaLath™ or 3/4" to 7/8" thick stuccobase with (optional) PermaLath™ 1000, followed by STUCCO PRIME and finished with SENERLASTIC™ PLUS siliconized elastomeric finish. All joints must be sealed with Sonneborn® Sonolastic150 sealant with VLM Technology—10 year limited material & labor warranty.  
-OR-

SENERGY STUCCOBASE applied per specification of 3/8" to 1/2" thick with (optional) PermaLath™ or 3/4" to 7/8" thick stuccobase with (optional) PermaLath™ 1000, followed by an application of ALPHA Base Coat and FLEXGUARD 4 Reinforcing Mesh and finished with one of the following options:

- A. SENERFLEX®, 100% acrylic polymer-based Finish and seal all joints with Sonneborn® Sonolastic150 sealant with VLM Technology—7-year limited material & labor warranty.
- B. SILCOAT™ silicone-enhanced 100% acrylic polymer-based Finish and seal all joints with Sonneborn® Sonolastic150 sealant with VLM Technology—7-year limited material & labor warranty
- C. SENERLASTIC™ Finish, acrylic-based elastomeric finish and seal all joints with Sonneborn® Sonolastic150 sealant with VLM Technology—10-year limited material & labor warranty  
All joints must be sealed with Sonneborn® Sonolastic150 sealant with VLM Technology.

## Stucco Coating System Warranties

Two coat application of cement plaster (3/4" to 7/8" thick) over approved substrates in accordance with ASTM C926 and PCA Plaster (Stucco) Manual and finished with one of the following options:

- A. SENERFLEX® Finish, 100% acrylic polymer-based finish—3-year coating warranty
- B. SILCOAT™ Finish, silicone-enhanced 100% acrylic polymer-based finish—3-year coating warranty
- C. SENERLASTIC™ Coating, 100% acrylic polymer-based coating—5-year coating warranty
- D. SENERLASTIC™ Finish, 100% acrylic polymer-based elastomeric finish—5-year coating warranty
- E. SENERLASTIC™ PLUS Coating, siliconized elastomeric coating—7-year coating warranty
- F. SENERLASTIC™ PLUS Finish, siliconized elastomeric finish—7-year coating warranty

# Stucco Systems Warranties and Requirements

## Warranty Notes

1. Contact Senergy® for information concerning applicator requirements for approval.
2. A Senergy Warranty Request form for the system used must be submitted by the Senergy distributor for the project prior to issuance of the warranty.
3. Obtain warranty approval from Senergy prior to bidding project. Project specifications and/or plans may be required for review by Senergy prior to approval of warranty.
4. Other warranties may be offered to meet a specific project specification. Consult Senergy prior to start of project if a special warranty is required.
5. Sample warranties are available upon request.

## Residential Policy

On one and two-family residential framed construction, BASF Wall Systems requires that the wall system selected be one that includes provisions for moisture drainage. The choices include Senturion® line of water managed EIFS, commercial Senerflex® Wall Systems integrating moisture management features, Senergy Stucco Wall System, and Senergy Cement-Board Stucco™ Systems. Senergy Exterior Surfacing Systems for insulating concrete forms are also acceptable. There are no exceptions to this policy. Under no circumstances will BASF Wall Systems warrant the use of any other system on this type of construction without expressed written authorization from BASF Wall Systems [Residential construction using EIFS on masonry (CMU) or poured concrete does not require the additional water management provisions described above.]

See the Senergy *Residential Policy Bulletin* for a more detailed discussion of this topic. Consult BASF Wall Systems Technical Services Department for specific recommendations concerning all other applications. Consult the Senergy web-site, [www.senergy.cc](http://www.senergy.cc) for additional information about products and systems and for updated literature.

## Disclaimer

This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, BASF disclaims all CONDITIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. BASF SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

## BASF Wall Systems

3550 St. Johns Bluff Road South  
Jacksonville, FL 32224-2614  
Phone 800 221 9255  
Fax 904 996 6300  
[www.senergy.cc](http://www.senergy.cc)