

# HOBO<sup>®</sup> ZW-001 Data Logger

# **Temperature Data Node**

The HOBO ZW-001 is an easy-to-deploy, single-channel wireless temperature data node featuring an integrated temperature sensor. It wirelessly transmits data in real time, reducing the costs and inconvenience associated with manual data offload.

### Supported Measurements:

Temperature



# Key Advantages:

- Wirelessly transmits real-time temperature data
- Compact size for easy deployment wherever data is needed
- Notifies you of alarm conditions via email or text messages
- Onboard buffer memory helps prevent data loss
- Powerful HOBOware® Pro software for organizing and viewing data (included with HOBO data receiver)

A complete system requires at least one wireless HOBO data node, HOBO data receiver, and HOBOware Pro software (included with HOBO ZW-RCVR). Depending on your system deployment, a HOBO data router (ZW-ROUTER) may be required.

# HOBO ZW-001 Data Logger Specifications

Buffer memory: approx. 5k measurements
Sample rate: 1 min to 18 hrs
Transmission rate: 2 min and greater
Power options: AC power adapter, battery backup
Measurement range: Temp: -20 to 70°C (-4 to 158°F) when line powered, -20 to 50°C (-4 to 122°F) when battery powered.
Accuracy: Temp: ±0.54°C typical over 0 to 50°C (±0.97° F over 32 to 122°F) when line powered, ±0.21°C over 0 to 50°C (±0.38°F over 32 to 122°F) when battery powered.

#### **Operating Range**

**Temp:** -20 to 50°C (-4 to 122°F) when battery powered, -20 to 70°C (-4 to 158°F) when line powered. **RH:** 5%-95% non-condensing

Resolution: Temp: 0.02° C @ 25° C (0.04° F @ 77° F) Response time: Temp: 5 min. in air moving 1 m/sec (3.3 ft/sec) Range: Approx. 100m (300ft.) depending on obstructions or interference Weight: 138g (4.87 oz) with batteries Dimensions: 96.5 x 108 x 28mm (3.8 x 4.25 x 1.1 in) Radio power: 1.6 mW (2 dBm) Wireless data standard: IEEE802.15.4 2.4 GHz band

**CE** - The CE Marking identifies this product as complying with all relevant directives in the European Union (EU)

#### **Contact Us**

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

- Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Onset Computer Corporation 470 MacArthur Boulevard Bourne, MA 02532